


Flat thickness 50mm



Selected mounting - for PDF file. Thread M14 (14mm)

Selected colour - for PDF file.  Black

Product description

Polishing Pad NAT is designed for efficient polishing of painted coatings. It is adapted to existing on the market polishing systems, which work with both rotary and orbital machines, wet and dry and speed range 300-2500rpm.

Black pad is designed to work with last step compounds. The structure of the foam quickly gives off heat. Application: Anti-Hologram paste and mechanical applying of polishes.

Type Flat thickness 50mm

Name M14 Polishing Pad, black

Size

150mm x 50mm

Index

PPHK2010150

Product properties

Main product features.

Foam:

- Optimal selected shapes
- The homogeneous structure of high strength
- Specially shaped surface
- proper hardness

Mounting:

- M14 handle is made of ABS plastic with high impact.

Connection:

- Adhesive is matched individually to the bonded substrates.
- Resistance to temperature, aqueous environment and organic solvents

The product shows the resistance to prolonged exposure to temperatures up to 110 ° C.

| Parameters | Value | Standard |
|------------------|-----------|-------------------|
| Density | 26 - 30 | kg/m ³ |
| Hardness 40% | 2 - 4 | kPa |
| Elongation | 350 | % |
| Tensile strength | 200 | kPa |
| Cell diameter | 440 - 520 | micron |

Technical drawing

