Honey



Selected mounting - for PDF file.	Velcro
Selected colour - for	Orange

Product description

PDF file.

HONEY polishing pad is an easier, faster and more enjoyable way to get the highest gloss of lacquer for the most demanding users.

Orange pad is designed for use with the first and second step polishing compounds. Foam structure maintains the paste on the surface of the pad what provides accurate developing of particles and full utilization of the paste.

The edges of the hexagonal blocks reduce the time of bringing the paint to the ideal state. Cuts help to control the temperature.

Dividing the working surface allows an easy operation with the entire pad. We recommend working with rotary machines in the rev range 600-2000rpm. Application: first and second polishing compounds and One Step compounds.

Honey Туре

Velcro HONEYCombination Polishing Pad,

Size	Index
150mm x 50mm	PVHO1030150
150mm x 25mm	PVLO1030150
135mm x 25mm	PVLO1030135
125mm x 25mm	PVLO1030125

Product properties

Main product features.

- Optimal selected shapes
- The homogeneous structure of high strength
- Specially shaped surface
- proper hardness

Mounting:

• Polyamide velor to ensure strong connection

- Adhesive is matched individually to the bonded substrates.
- Resistance to temperature, aqueous environment and organic solvents

The product shows the resistance to prolonged exposure to temperatures up to 110 $^{\circ}$ C.

Parameters	Value	Standard
Density	36 - 41	kg/m3
Hardness 40%	8 - 11	kPa
Elongation	140	%
Tensile strength	200	kPa
Celldiameter	480 - 660	micron
Tear resistance	7	N/cm

Technical drawing





