


Flat thickness 25mm



Selected mounting - for PDF file. Velcro

Selected colour - for PDF file.  Blue

Product description

Polishing Pad NAT is designed for efficient polishing of painted coatings. It is adapted to existing on the market polishing systems, which work with both rotary and orbital machines, wet and dry and speed range 300-2500rpm.

Blue pad is designed for use with first step polishing compounds and compounds for matting. Foam structure is characterized by high aggressiveness which helps to permanently remove deep scratches while preparing surfaces for subsequent stages of paint correction. Usage: to enhance the effect of cutting for the polishing compounds.

Type Flat thickness 25mm

Name Velcro Polishing Pad, blue

Size	Index
150mm x 25mm	PVLB1010150
135mm x 25mm	PVLB1010135
125mm x 25mm	PVLB1010125
83mm x 25mm	PVLB1010083

Product properties

Main product features.

Foam:

- Optimal selected shapes
- The homogeneous structure of high strength
- Specially shaped surface
- proper hardness

Mounting:

- Polyamide velor to ensure strong connection

Connection:

- Adhesive is matched individually to the bonded substrates.
- Resistance to temperature, aqueous environment and organic solvents

The product shows the resistance to prolonged exposure to temperatures up to 110 ° C.

Parameters	Value	Standard
Density	36 - 41	kg/m ³
Hardness 40%	8 - 11	kPa
Elongation	200	%
Tensile strength	200	kPa
Cell diameter	600 - 800	micron
Tear resistance	7	N/cm

Technical drawing

