


Flat thickness 50mm



Selected mounting - for PDF file. Velcro

Selected colour - for PDF file.  Orange plus

Product description

Polishing Pad NAT is designed for efficient polishing of painted coatings. It is adapted to existing on the market polishing systems, which work with both rotary and orbital machines, wet and dry and speed range 300-2500rpm.

Orange pad is designed for use with first and second step polishing compounds. Foam structure maintains the paste on the surface of the sponge what provides accurate developing particles and full utilization of the paste.

Application: polishing compounds from cutting to polishing type.

Type Flat thickness 50mm

Name Velcro Polishing Pad, orange plus

Size

150mm x 50mm

Index

PVHO3110150

Product properties

Main product features.

Foam:

- Optimal selected shapes
- The homogeneous structure of high strength
- Specially shaped surface
- proper hardness

Mounting:

- Polyamide velor to ensure strong connection

Connection:

- Adhesive is matched individually to the bonded substrates.
- Resistance to temperature, aqueous environment and organic solvents

The product shows the resistance to prolonged exposure to temperatures up to 110 ° C.

Parameters	Value	Standard
Density	27 - 30	kg/m ³
Hardness 40%	4,5 - 6,5	kPa
Cell diameter	435 - 588	micron

Technical drawing

