

## Flat thickness 25mm



Selected mounting - for PDF file. Velcro

Selected colour - for PDF file. ● Red

### Product description

Polishing Pad NAT is designed for efficient polishing of painted coatings. It is adapted to existing on the market polishing systems, which work with both rotary and orbital machines, wet and dry and speed range 300-2500rpm.

Red pad is made for faster surface finishing when working with hard coatings.

Application: compounds gently polishing, finishing and to work with cleaners.

Type Flat thickness 25mm

Name Velcro Polishing Pad, red

Size	Index
150mm x 25mm	PVLR1010150
135mm x 25mm	PVLR1010135
125mm x 25mm	PVLR1010125
83mm x 25mm	PVLR1010083

### Product properties

#### Main product features.

##### Foam:

- Optimal selected shapes
- The homogeneous structure of high strength
- Specially shaped surface
- proper hardness

##### Mounting:

- Polyamide velor to ensure strong connection

##### Connection:

- Adhesive is matched individually to the bonded substrates.
- Resistance to temperature, aqueous environment and organic solvents

The product shows the resistance to prolonged exposure to temperatures up to 110 ° C.

Parameters	Value	Standard
Density	38 - 47	kg/m <sup>3</sup>
Hardness 40%	5,5 - 8,5	kPa
Elongation	350	%
Tensile strength	300	kPa
Tear resistance	9	N/cm

### Technical drawing

