

Flat thickness 25mm



Selected mounting - for PDF file. **Velcro**

Selected colour - for PDF file. **Swap White**

Product description

Polishing Pad NAT is designed for efficient polishing of painted coatings. It is adapted to existing on the market polishing systems, which work with both rotary and orbital machines, wet and dry and speed range 300-2500rpm.

Swap pad is designed for use with first step polishing compounds and compounds for matting. Foam structure is characterized by high aggressiveness which helps to permanently remove deep scratches while preparing surfaces for subsequent stages of paint correction. Usage: to enhance the effect of cutting for the polishing compounds.

Type Flat thickness 25mm

Name Velcro Polishing Pad, Swap white

Size	Index
150mm x 50mm	PVLH2310150
150mm x 25mm	PVLH2310150
135mm x 25mm	PVLH2310135
125mm x 25mm	PVLH2310125
83mm x 25mm	PVLH2310083

Product properties

Main product features.

Foam:

- Optimal selected shapes
- The homogeneous structure of high strength
- Specially shaped surface
- proper hardness

Mounting:

- Polyamide velor to ensure strong connection

Connection:

- Adhesive is matched individually to the bonded substrates.
- Resistance to temperature, aqueous environment and organic solvents

The product shows the resistance to prolonged exposure to temperatures up to 110 ° C.

Parameters	Value	Standard
Density	39 - 43	kg/m ³
Hardness 40%	50 - 54	kPa
Elongation	100	%
Tensile strength	569	kPa

Technical drawing

