


Flat thickness 50mm



Selected mounting - for PDF file. Velcro

Selected colour - for PDF file.  White plus

Product description

Polishing Pad NAT is designed for efficient polishing of painted coatings. It is adapted to existing on the market polishing systems, which work with both rotary and orbital machines, wet and dry and speed range 300-2500rpm. White pad is designed for use with first and second step polishing compounds. Foam structure maintains the compound on the surface of the sponge which provides accurate developing particles and full utilization of the compound. Application: polishing compounds from cutting to polishing type.

Type Flat thickness 50mm

Name Velcro Polishing Pad, white plus

Size

150mm x 50mm

Index

PVHW3010150

Product properties

Main product features.

Foam:

- Optimal selected shapes
- The homogeneous structure of high strength
- Specially shaped surface
- proper hardness

Mounting:

- Polyamide velor to ensure strong connection

Connection:

- Adhesive is matched individually to the bonded substrates.
- Resistance to temperature, aqueous environment and organic solvents

The product shows the resistance to prolonged exposure to temperatures up to 110 ° C.

Parameters

Value

Standard

Density

36 - 40

kg/m³

Hardness 40%

6,5 - 9,5

kPa

Elongation

90

%

Tensile strength

190

kPa

Cell diameter

475 - 665

micron

Technical drawing

