

Waffle



Selected mounting - for PDF file. Velcro

Selected colour - for PDF file. Black

Product description

Polishing Pad NAT is designed for efficient polishing of painted coatings. It is adapted to existing on the market polishing systems, which work with both rotary and orbital machines, wet and dry and speed range 300-2500rpm. Black pad is designed for use with last step compounds. The structure of the foam quickly gives off heat. Application: Anti-Hologram paste and mechanical applying of polishes. Specific shape minimizes signs of spin / holograms. For using the features of this product effectively we recommend working with less downforce for preventing flattening of the work surface.

Type Waffle

Name Waffle Velcro Polishing Pad, black

Size	Index
150mm x 25mm	PVLK2020150
135mm x 25mm	PVLK2020135
125mm x 25mm	PVLK2020125
83mm x 25mm	PVLK2020083

Product properties

Main product features.

Foam:

- Optimal selected shapes
- The homogeneous structure of high strength
- Specially shaped surface
- proper hardness

Mounting:

- Polyamide velor to ensure strong connection

Connection:

- Adhesive is matched individually to the bonded substrates.
- Resistance to temperature, aqueous environment and organic solvents

The product shows the resistance to prolonged exposure to temperatures up to 110 ° C.

Parameters	Value	Standard
Density	26 - 30	kg/m ³
Hardness 40%	2 - 4	kPa
Elongation	350	%
Tensile strength	200	kPa
Cell diameter	440 - 520	micron

Technical drawing

