

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.04.2013

Version number 2

Revision: 16.04.2013

## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** YÜKSEK SICAKLIĐA DAYANIKLI AST SÝY.
- **Article number:** 4254KASBD
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the preparation** Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Manufacturer: Kansai Altan Boya San. ve Tic. A.S.  
Ankara Asfalti 25. Km.  
TR-35730 Kemalpaşa - İzmir  
TURKEY  
sevde.bozacioglu@kansaialtan.com.tr
- **Further information obtainable from:** Material safety department
- **Emergency telephone number:**  
During working hours: +90 232 870-1277

## 2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361d Suspected of damaging the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R20/21-40: Harmful by inhalation and in contact with skin. Limited evidence of a carcinogenic effect.



Xi; Irritant

R38: Irritating to skin.



Xi; Sensitising

R43: May cause sensitisation by skin contact.

R10: Flammable.

(Contd. on page 2)

EU

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.04.2013

Version number 2

Revision: 16.04.2013

**Trade name: YÜKSEK SICAKLIĐA DAYANIKLI AST SÝY.**

(Contd. of page 1)

- **Information concerning particular hazards for human and environment:**  
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- **Classification system:**  
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

- **Labelling according to EU guidelines:**  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**






Xn Harmful

- **Hazard-determining components of labelling:**  
2-butanone oxime  
xylene
- **Risk phrases:**  
10 Flammable.  
20/21 Harmful by inhalation and in contact with skin.  
38 Irritating to skin.  
40 Limited evidence of a carcinogenic effect.  
43 May cause sensitisation by skin contact.
- **Safety phrases:**  
9 Keep container in a well-ventilated place.  
23 Do not breathe gas/fumes/vapour/spray .  
36/37 Wear suitable protective clothing and gloves.  
51 Use only in well-ventilated areas.  
60 This material and its container must be disposed of as hazardous waste.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene  Xn R20/21;  Xi R38 R10 <hr style="border-top: 1px dashed black;"/>  Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
---	--	--------

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.04.2013

Version number 2

Revision: 16.04.2013

**Trade name: YÜKSEK SICAKLIĐA DAYANIKLI AST SÝY.**

(Contd. of page 2)

CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene ☒ Xn R20; ☒ F R11 ☒ Flam. Liq. 2, H225; ☒ Acute Tox. 4, H332	3-<10%
CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-00-3	toluene ☒ Xn R48/20-63-65; ☒ Xi R38; ☒ F R11 R67 Repr. Cat. 3 ☒ Flam. Liq. 2, H225; ☒ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; ☒ Skin Irrit. 2, H315; STOT SE 3, H336	3-<5%
CAS: 96-29-7 EINECS: 202-496-6 Index number: 616-014-00-0	2-butanone oxime ☒ Xn R21-40; ☒ Xi R41; ☒ Xi R43 Carc. Cat. 3 ☒ Carc. 2, H351; ☒ Eye Dam. 1, H318; ☒ Acute Tox. 4, H312; Skin Sens. 1, H317	1-≤2,5%
CAS: 27253-31-2 EINECS: 248-373-0	neodecanoic acid, cobalt salt ☒ Xn R22; ☒ Xi R43; ☒ N R51/53 ☒ Aquatic Chronic 2, H411; ☒ Acute Tox. 4, H302; Skin Sens. 1, H317	0,1-<0,3%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

#### 4 First aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

#### 5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:**

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

#### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

EU

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.04.2013

Version number 2

Revision: 16.04.2013

**Trade name: YÜKSEK SICAKLIĐA DAYANIKLI AST SÝY.**

(Contd. of page 3)

- **Environmental precautions:**
  - Do not allow product to reach sewage system or any water course.
  - Inform respective authorities in case of seepage into water course or sewage system.
  - Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
  - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
  - Dispose contaminated material as waste according to item 13.
  - Ensure adequate ventilation.
  - Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
  - Ensure good ventilation/exhaustion at the workplace.
  - Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
  - Keep ignition sources away - Do not smoke.
  - Protect from heat.
  - Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** 5 °C - 40 °C
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
  - Keep container tightly sealed.
  - Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
  - The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

### 1330-20-7 xylene

IOELV	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin
-------	--

### 100-41-4 ethylbenzene

IOELV	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm Long-term value: 442 mg/m <sup>3</sup> , 100 ppm Skin
-------	---

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
  - Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.04.2013

Version number 2

Revision: 16.04.2013

**Trade name: YÜKSEK SICAKLIĐA DAYANIKLI AST SÝY.**

(Contd. of page 4)

*Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.*

*Avoid contact with the skin.*

*Avoid contact with the eyes and skin.*

**· Respiratory protection:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.*

**· Recommended filter device for short term use:** *Combination filter A-P2*

**· Protection of hands:**



*Protective gloves*

*Sensibilization by the components in the glove materials is possible.*

*Check protective gloves prior to each use for their proper condition.*

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

*Use gloves resistant to chemical affects (EN 374) and having CE marking.*

**· Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.*

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

**· Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

**· For the permanent contact gloves made of the following materials are suitable:**

*Butyl rubber, BR*

*Fluorocarbon rubber (Viton)*

**· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

*Neoprene gloves*

**· As protection from splashes gloves made of the following materials are suitable:** *Nitrile rubber, NBR*

**· Eye protection:**



*Tightly sealed goggles*

**· Body protection:** *Use protective clothing that prevents direct contact to skin.*

**· Protective suit antistatic.**

## 9 Physical and chemical properties

**· Information on basic physical and chemical properties**

**· General Information**

**· Appearance:**

**Form:** *Fluid*

**Colour:** *Black*

**· Odour:** *Characteristic*

(Contd. on page 6)

EU

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.04.2013

Version number 2

Revision: 16.04.2013

**Trade name: YÜKSEK SICAKLIĐA DAYANIKLI AST SÝY.**

(Contd. of page 5)

· <b>Odour threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	136 °C
· <b>Flash point:</b>	21 °C (Closed cup)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	430 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	1,1 Vol %
<b>Upper:</b>	7,0 Vol %
· <b>Vapour pressure at 20 °C:</b>	6,7 hPa
· <b>Density at 20 °C:</b>	1,09 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Partly soluble.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

**1330-20-7 xylene**

Dermal	LD50	2000 mg/kg (rabbit)
--------	------	---------------------

**100-41-4 ethylbenzene**

Dermal	LD50	17800 mg/kg (rabbit)
--------	------	----------------------

(Contd. on page 7)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.04.2013

Version number 2

Revision: 16.04.2013

**Trade name: YÜKSEK SICAKLIĐA DAYANIKLI AST SÝY.**

(Contd. of page 6)

**108-88-3 toluene**

Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

**96-29-7 2-butanone oxime**

Dermal	LD50	200-2000 mg/kg (rat)
Inhalative	LC50/4 h	20 mg/l (rat)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behaviour in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
----------	---

08 01 00	wastes from MFSU and removal of paint and varnish
----------	---

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
-----------	---

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
----------	---

08 01 00	wastes from MFSU and removal of paint and varnish
----------	---

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.04.2013

Version number 2

Revision: 16.04.2013


**Trade name: YÜKSEK SICAKLIĐA DAYANIKLI AST SÝY.**

(Contd. of page 7)

08 01 13*	sludges from paint or varnish containing organic solvents or other dangerous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by dangerous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· UN-Number	UNI263
· ADR, IMDG, IATA	
· UN proper shipping name	1263 PAINT, special provision 640D
· ADR	PAINT
· IMDG, IATA	
· Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· Packing group	II
· ADR, IMDG, IATA	
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E, S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	2
· Tunnel restriction code	D/E
· UN "Model Regulation":	UNI263, PAINT, special provision 640D, 3, II

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Labelling according to EU guidelines:  
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 9)

EU



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.04.2013

Version number 2

Revision: 16.04.2013

**Trade name: YÜKSEK SICAKLIĐA DAYANIKLI AST SÝY.**

(Contd. of page 8)

· **Code letter and hazard designation of product:**



Xn Harmful

· **Hazard-determining components of labelling:**

2-butanone oxime  
xylene

· **Risk phrases:**

10 Flammable.  
20/21 Harmful by inhalation and in contact with skin.  
38 Irritating to skin.  
40 Limited evidence of a carcinogenic effect.  
43 May cause sensitisation by skin contact.

· **Safety phrases:**

9 Keep container in a well-ventilated place.  
23 Do not breathe gas/fumes/vapour/spray .  
36/37 Wear suitable protective clothing and gloves.  
51 Use only in well-ventilated areas.  
60 This material and its container must be disposed of as hazardous waste.  
· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.  
R10 Flammable.  
R11 Highly flammable.  
R20 Harmful by inhalation.  
R20/21 Harmful by inhalation and in contact with skin.  
R21 Harmful in contact with skin.  
R22 Harmful if swallowed.  
R38 Irritating to skin.  
R40 Limited evidence of a carcinogenic effect.  
R41 Risk of serious damage to eyes.  
R43 May cause sensitisation by skin contact.  
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R63 Possible risk of harm to the unborn child.

(Contd. on page 10)

EU

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.04.2013

Version number 2

Revision: 16.04.2013

**Trade name: YÜKSEK SICAKLIĐA DAYANIKLI AST SÝY.**

(Contd. of page 9)

R65 *Harmful: may cause lung damage if swallowed.*

R67 *Vapours may cause drowsiness and dizziness.*

· **Department issuing MSDS:** Product safety department

· **Contact:** Ms. Sevede Seza Bozaciođlu

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

LD50: Lethal dose, 50 percent

· **\* Data compared to the previous version altered.**

EU