

Printing date 30.01.2013 Version number 3 Revision: 30.01.2013

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: KEMÝPOKS FOSFAT FÝLLER GRÝ
- · Article number: BA12G212BD
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the preparation Paint
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer: Kansai Altan Boya San. ve Tic. A.S.

Ankara Asfalti 25. Km.

TR-35730 Kemalpasa - Izmir

TURKEY

sevde.bozacioglu@kansaialtan.com.tr

- · Further information obtainable from: Material safety department
- · Emergency telephone number:

During working hours: +90 232 870-1277

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

×

Xi; Irritant

R36/38: Irritating to eyes and skin.

×

Xi; Sensitising

R43: May cause sensitisation by skin contact.

*

N; Dangerous for the environment

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 2)

E





Printing date 30.01.2013 Version number 3 Revision: 30.01.2013

Trade name: KEMÝPOKS FOSFAT FÝLLER - GRÝ

(Contd. of page 1)

R10: Flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





Xi Irritant

N Dangerous for the environment

· Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

· Risk phrases:

10 Flammable.

36/38 Irritating to eyes and skin.

- 43 May cause sensitisation by skin contact.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Safety phrases:

- 23 Do not breathe gas/fumes/vapour/spray.
- 24/25 Avoid contact with skin and eyes.
- 37 Wear suitable gloves.
- 51 Use only in well-ventilated areas.
- 57 Use appropriate container to avoid environmental contamination.

· Special labelling of certain preparations:

Contains epoxy constituents. See information supplied by the manufacturer.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9

xylene

 $\overline{R10}$

🗶 Xn R20/21; 🗶 Xi R38

♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315

(Contd. on page 3)

10-<20%

EU





Printing date 30.01.2013 Version number 3 Revision: 30.01.2013

Trade name: KEMÝPOKS FOSFAT FÝLLER - GRÝ

		ntd. of page
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) Xi R36/38; Xi R43; N R51/53 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-<25%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene X Xn R20;	3-<10%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol R10-67 ♠ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	3-<10%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6	trizinc bis(orthophosphate) N R50/53 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	3-<10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6	butan-1-ol Xn R22; Xi R37/38-41 R10-67 Flam. Liq. 3, H226; Eye Dam. 1, H318; ↑ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	3-<5%
CAS: 78-83-1 EINECS: 201-148-0 Index number: 603-108-00-1	2-methylpropan-1-ol Xi R37/38-41 R10-67 Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-≤2,5%
	zinc oxide N R50/53 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 the wording of the listed risk phrases refer to section 16.	0,3-<1%

4 First aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

(Contd. on page 4)







Printing date 30.01.2013 Version number 3 Revision: 30.01.2013

Trade name: KEMÝPOKS FOSFAT FÝLLER - GRÝ

(Contd. of page 3)

Wear fully protective suit.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage: 5 °C 40 °C
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

1330-20-7 x	ylene
-------------	-------

IOELV Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

(Contd. on page 5)







Printing date 30.01.2013 Version number 3 Revision: 30.01.2013

Trade name: KEMÝPOKS FOSFAT FÝLLER - GRÝ

	(Contd. of page 4)		
100-41	4 ethylbenzene		
<i>IOELV</i>	Short-term value: 884 mg/m³, 200 ppm		
	Long-term value: 442 mg/m³, 100 ppm		
	Skin		
<i>107-98</i> ·	107-98-2 1-methoxy-2-propanol		
<i>IOELV</i>	Short-term value: 568 mg/m³, 150 ppm		
	Long-term value: 375 mg/m³, 100 ppm		
	Skin		

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Recommended filter device for short term use: Combination filter A-P2
- · Protection of hands:



Protective gloves

Sensibilization by the components in the glove materials is possible.

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Use gloves resistant to chemical affects (EN 374) and having CE marking.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Fluorocarbon rubber (Viton)

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Neoprene gloves

- · As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
- · Eye protection:



Tightly sealed goggles

(Contd. on page 6)





Printing date 30.01.2013 Version number 3 Revision: 30.01.2013

Trade name: KEMÝPOKS FOSFAT FÝLLER - GRÝ

(Contd. of page 5)

- · **Body protection:** Use protective clothing that prevents direct contact to skin.
- · Protective suit antistatic.

9 Physical and chemical properties

· Information	on basic	physical	and chemi	cal properties

· General Information

· Appearance:

Form: Fluid Colour: Grey

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 136 °C

• Flash point: 24 °C (Closed cup)

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 500 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

 Lower:
 1,1 Vol %

 Upper:
 7,0 Vol %

 • Vapour pressure at 20 °C:
 6,7 hPa

Density at 20 °C: 1,56 g/cm³
 Relative density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

vater: Partly soluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic at 20 °C: 320 mm²/s

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 7)





Printing date 30.01.2013 Version number 3 Revision: 30.01.2013

Trade name: KEMÝPOKS FOSFAT FÝLLER - GRÝ

(Contd. of page 6)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 1	values rele	vant for classification:	
1330-20-7	1330-20-7 xylene		
Dermal	LD50	2000 mg/kg (rabbit)	
100-41-4 е	100-41-4 ethylbenzene		
Dermal	LD50	17800 mg/kg (rabbit)	
107-98-2 1	-methoxy-	2-propanol	
Dermal	LD50	13000 mg/kg (rabbit)	
Inhalative	LC50/4 h	6 mg/l (rat)	
71-36-3 bu	71-36-3 butan-1-ol		
Dermal	LD50	3400 mg/kg (rabbit)	
Inhalative	LC50/4 h	8000 mg/l (rat)	
78-83-1 2-	78-83-1 2-methylpropan-1-ol		
Dermal	LD50	3400 mg/kg (rabbit)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 3 and 15 for details.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.

(Contd. on page 8)





Printing date 30.01.2013 Version number 3 Revision: 30.01.2013

Trade name: KEMÝPOKS FOSFAT FÝLLER - GRÝ

(Contd. of page 7)

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	waste catalogue
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS
	AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 13*	sludges from paint or varnish containing organic solvents or other dangerous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	packaging containing residues of or contaminated by dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
· ADR, IMDG, IATA	UN1263
UN proper shipping name	
$\cdot ADR$	1263 PAINT, special provision 640E
· IMDG	PAINT (reaction product: bisphenol-A-(epichlorhydrin) epox resin (number average molecular weight \leq 700), trizin bis(orthophosphate)), MARINE POLLUTANT
· IATA	PAINT
· Transport hazard class(es) · ADR, IMDG, IATA	
- · · · · · · · · · · · · · · · · · · ·	3 Flammable liquids.
ADR, IMDG, IATA	3 Flammable liquids. 3
· ADR, IMDG, IATA · Class · Label	
· ADR, IMDG, IATA · Class	
· ADR, IMDG, IATA · Class · Label · Packing group	3





Printing date 30.01.2013 Version number 3 Revision: 30.01.2013

Trade name: KEMÝPOKS FOSFAT FÝLLER - GRÝ

	(Contd. of page 8)
· Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	30
· EMS Number:	F-E, <u>S-E</u>
Transport in bulk according to Annex II MARPOL73/78 and the IBC Code	· ·
	Not applicable.
· Transport/Additional information:	
$\cdot ADR$	
· Limited quantities (LQ)	5L
· Transport category	3
· Tunnel restriction code	D/E

15 Regulatory information

· UN "Model Regulation":

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

UN1263, PAINT, special provision 640E, 3, III

· Code letter and hazard designation of product:





Xi Irritant

N Dangerous for the environment

· Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)

- · Risk phrases:
 - 10 Flammable.
- 36/38 Irritating to eyes and skin.
- 43 May cause sensitisation by skin contact.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- · Safety phrases:
 - 23 Do not breathe gas/fumes/vapour/spray.
- 24/25 Avoid contact with skin and eyes.
- 37 Wear suitable gloves.
- 51 Use only in well-ventilated areas.
- 57 Use appropriate container to avoid environmental contamination.
- · Special labelling of certain preparations:

Contains epoxy constituents. See information supplied by the manufacturer.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.

(Contd. on page 10)





Printing date 30.01.2013 Version number 3 Revision: 30.01.2013

Trade name: KEMÝPOKS FOSFAT FÝLLER - GRÝ

(Contd. of page 9)

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R11 Highly flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R22 Harmful if swallowed.
- R36/38 Irritating to eyes and skin.
- R37/38 Irritating to respiratory system and skin.
- R38 Irritating to skin.
- R41 Risk of serious damage to eyes.
- *R43* May cause sensitisation by skin contact.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: Product safety department
- · Contact: Ms. Sevde Seza Bozacioğlu
- · Abbreviations and acronyms:
- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organization
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- LD50: Lethal dose, 50 percent
- * * Data compared to the previous version altered.

