



TECHNICAL INFORMATION HAMERPAINT 3 in 1

Description: Decorative finishing alkyd paint with wrought iron effect that has good adhesion to metal surfaces. Dries fast, supple, glossy effect. Contains modified styrene.

Technical data:

Flash Point: < 21 ° C

Solubility: 60 ± 5%

Density: 1.00-1.25 gr/cm³

Viscosity: 65-75 KU

Application areas: This product is suitable for all kinds of machines and accessories agricultural and household tools, steel doors, cabinets, tables, desks.

Application:

a) Thinner: Nitrocellulose Thinner (% 15-20)

b) Preparation of povahnostta: The surface should be thoroughly cleaned of dust, oil and other contaminants.

c) Application: After dilution hamershlaka apply by brush, roller or spray on the metal surface. The product covers imperfections well surface, giving a decorative look. To achieve better protection rust hamershlakat is recommended to be applied to alkyd primer. Use after reaching the required viscosity (25-35 sec DIN CUP 4/20°C). For better coating properties first layer should be fine, but the next one is more dense. The intensity of the effect of wrought iron can give the viscosity of the preparation, air pressure and distance between the gun and the surface itself.

Coverage: 10-12 m² / RT (one layer)

Drying at 25 ° C:

a) Keep dust: 30 - 60 minutes

b) Touch dry: 15 - 20 minutes

c) Complete drying (stick): 24 hours

Storage: At room temperature in the original container, one year.

Packaging: 0.750 l, 2.5 l

Note: Keep away from sources of ignition. Keep out of reach of children