

Banja Komerc Bekament DOO	PRODUCT DATA SHEET	Edition 1	Date: June 18 2015
		Version 4	
BK-NIVELATOR			RZ-TLP-049

1. PRODUCT AND COMPANY INFORMATION

Product commercial name: BK-Nivelator

Manufacturer: Banja Komerc Bekament DOO
34304 Banja
Arandelovac
tel. 034-6777-500
fax. 034-6777-505
email: komercijala@bekament.com

PDS contact: email: laboratorija@bekament.com

2. DESCRIPTION, FIELD OF APPLICATION

BK-Nivelator is a depth primer used for leveling and neutralizing unevenly absorbing surfaces, such as gas concrete, brick, porous rock, etc. It is used as a primer for highly absorbent surfaces when applying cement-lime and gypsum-lime machine mortars with the aim of preventing uneven drying and cracking of the mortar due to premature absorption of moisture by the base. It is also used as a primer before smoothing out the area using lime, gypsum, or organic-based plasters. The dry spread is colorless and has no negative side effects to the vapor conductivity of the system. The primer does not form a film and does not solidify the base.

It is considered an eco-product not harmful to human health or the environment. It does not contain organic solvents.

3. COMPOSITION

Chemical composition: Water, higher fatty acids ether emulsion, additives.

Hazardous substances: In accordance with the (EC) Regulation No. 1272/2008 on classification, labelling and packaging of substances and mixtures, through which the CLP/GHS classification and labeling system was introduced into law, this product is not classified as a hazardous product.

4. TECHNICAL CHARACTERISTICS

density, g/dm ³ (EN ISO 2811-1)	1,000-1,050
Viscosity, mPas (EN ISO 2555)	< 100
Particle size, µm (EN 1524)	< 100 (fine according to EN 13300)
Consumption, g/m ²	~30-60
Packaging, kg	10; 20;

Banja Komerc	PRODUCT DATA	Edition 1	Date: June 18 2015
--------------	--------------	-----------	--------------------

Bekament DOO	SHEET	Version 4	
BK-NIVELATOR			RZ-TLP-049

5. OTHER CHARACTERISTICS

Physical appearance: Whitish liquid

Odor: Mild

pH value (EN ISO 787-9): 7-7.5

Dry matter content (EN ISO 3251), %: ~15

VOC* content, g/l: < 1 (maximum value allowed A (g) 30 g/l)

*VOC: Volatile Organic Compound;

6. BASIS

The surface to which the basis is applied must be firm, clean, and dry, without poorly bound parts, greasy stains, etc. All gas concrete, brick, porous concrete surfaces, as well as cement-lime mortars, gipsum-lime mortars, etc. are appropriate surfaces. All old mortars and spreads which did not take proper hold must be removed.

7. PREPARATION AND APPLICATION

Stirr the contents of the bucket well before use. BK-Nivelator is prepared by diluting it in water in a 1:6 to 1:10 ratio, depending on the absorption of the surface. The product should be diluted to a lesser extent when it comes to absorbent bases. The spread is applied using a roller, brush, or machine spraying using appropriate equipment. When dealing with highly absorbent surfaces, the product may be applied twice according to the wet-on-wet principle.

Air and basis temperature during installation should be in the +5 °C to +30 °C range. Do not work under direct sunlight, wind, or rain.

8. CLEANING THE TOOLS

All tools must be thoroughly washed using water immediately after use. If the tools are not washed immediately after use, remove the hardened mechanical residue.

9. HANDLING AND STORAGE

No special caution during use is needed when using the product properly. Keep out of reach of children.

Store at temperatures between +5 ° C and +25 ° C, protected from direct sunlight and frost.

Shelf life: 18 months.

10. PERSONAL PROTECTION

Respiratory tract protection: Not needed when the rooms are well aerated.

Hands and body protection: When the skin is repeatedly exposed to the mass, a preventative use of protection gloves is recommended. Use long-sleeve work overalls.

Eye protection: Use safety goggles as a preventative measure.

Banja Komerc Bekament DOO	PRODUCT DATA SHEET	Edition 1	Date: June 18 2015
		Version 4	
BK-NIVELATOR			RZ-TLP-049

11. ECOTOXICOLOGICAL INFORMATION

Based on experiences and information currently available, no negative health effects are known when the product is used appropriately. Prevent uncontrolled discharge into sewage and waterways.

12. STORAGE

In accordance with local/regional/European/national regulations.

13. OTHER INFORMATION

If the contractor notices an aesthetic or application deficiency while using the material, he is obliged to cease the works and notify the manufacturer of this. The manufacturer will consider the claim in the shortest possible time frame. Complaints to the manufacturer upon using a significant portion or the entire amount of the materials are not subject to claims.

14. NOTE

Banja Komerc Bekament DOO performs product quality checks using its own laboratories. It also regularly tests its products in certified laboratories. The Data Sheet is the product of our knowledge and previous practical experience. The purpose of the Data Sheet is to serve as a recommendation in order to achieve the best possible results. If weather and other conditions are different than those described in our instructions, our instructions need to be taken as general guidelines, without an installation warranty.

Banka Komerc Bekament DOO assumes no liability for damages resulting from the improper use or incorrect product selection, as well as for poorly executed work. It is assumed that the contractor has mastered the techniques of installing and use of various products.

Matters written herein bind us in no way.

Date: August 11 2014

Previous version: Version 2- February 9 2013

Amended chapters: 3, 12.