

# Declaration of Performance

According to the EU Regulation, CPR 305/2011

## DoP No. 070 BK-HidroStop 5/5

1. Unique identification code of the product-type:

**BK-HidroStop 5/5**

2. Type, batch or serial number or any other element allowing identification of the construction product:

**Printed on the packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Two-component hydro-insulation polymer-cement based coating**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

**Banja Komerc Bekament DOO, Banja, RS-34304 Arandjelovac, Serbia**

5. Name and contact address of the authorised representative:

Ada Color Ltd

Bulgaria, Plovdiv 4003

176 'Brezovsko Shose' Str.

6. System of assessment and verification of constancy of performance of the construction product :

**System 3**

7. Declaration of Performance of building product BK-HidroStop 5/5 is covered by a harmonised standard:

**EN 14891:2012**

Initial product type testing was carried out by Research Institute for Building Materials, Sofia (Bulgaria)(Research Institute for Building Materials, Sofia, Bulgaria, NB: 1950) and Test Report no. 1113-1; ITT-EC-292-7/2014 was issued.

8. Declared performance:

Classification per EN 14891:2012: CM P

Essential Characteristics	Performance	Harmonised technical specification
Adhesion after conditioning under normal conditions	$\geq 0,5 \text{ N/mm}^2$	EN 14891
Adhesion after water conditioning	$\geq 0,5 \text{ N/mm}^2$	EN 14891
Adhesion after conditioning at elevated temperatures	$\geq 0,5 \text{ N/mm}^2$	EN 14891
Adhesion after freeze/thaw cycle	$\geq 0,5 \text{ N/mm}^2$	EN 14891
Adhesion after contact with chlorinated water	$\geq 0,5 \text{ N/mm}^2$	EN 14891
Watertightness	Watertight at 168 h at 150 kPa, $\leq 20\text{g}$ weight gain	EN 14891
Crack-bridging ability	$\geq 0,75 \text{ mm}$	EN 14891
Reaction to fire	NPD	EN 13501-1
Durability (frost resistance)	NPD	EN 1015-21

9. Essential Characteristics of BK-HidroStop 5/5 are in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Name and function:

Biljana Kamaljevic, Development Department Manager

Place and date:

Arandjelovac, 20 June 2015

SIGNATURE AND STAMP