

# Declaration of Performance

According to the EU Regulation, CPR 305/2011

## DoP No. 016-02 BK-HidroStop Extra

1. Unique identification code of the product-type:

**BK-HidroStop Extra**

2. Type, batch or serial number or any other element allowing identification of the construction product:

**Printed on the packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Single-component flexible hydro-insulation polymer-cement based coating**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

**Banja Komerc Bekament DOO, Banja, RS-34304 Arandjelovac, Serbia**

5. Name and contact address of the authorised representative:

ADA COLOR Ltd , 176 Brezovsko Shose, Plovdiv

6. System of assessment and verification of constancy of performance of the construction product  
:

**System 3**

7. Declaration of Performance of building product BK-HidroStop Extra is covered by a harmonised standard:

**EN 14891:2012**

Initial product type testing was carried out by Research Institute for Building Materials, Sofia (Bulgaria)(Research Institute for Building Materials, Sofia, Bulgaria, NB: 1950) and Test Report no. 945-1; ITT-EC-292-6/2014 was issued.

1. Declared performance:

Classification per EN 14891:2012: CM P

Essential Characteristics	Performance	Harmonised technical specification
Adhesion after conditioning under normal conditions	$\geq 0,5 \text{ N/mm}^2$	EN 14891
Adhesion after water conditioning	$\geq 0,5 \text{ N/mm}^2$	EN 14891
Adhesion after conditioning at elevated temperatures	$\geq 0,5 \text{ N/mm}^2$	EN 14891
Adhesion after freeze/thaw cycle	$\geq 0,5 \text{ N/mm}^2$	EN 14891
Adhesion after contact with chlorinated water	$\geq 0,5 \text{ N/mm}^2$	EN 14891
Watertightness	Watertight at 168 h at 150 kPa, $\leq 20\text{g}$ weight gain	EN 14891
Crack-bridging ability	$\geq 0,75 \text{ mm}$	EN 14891
Reaction to fire	NPD	EN 13501-1
Durability (frost resistance)	NPD	EN 1015-21

9. Essential Characteristics of BK-HidroStop Extra are in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Name and function:

Biljana Kamaljevic, Development Department Manager

Place and date:

Arandjelovac, 20 June 2015

SIGNATURE AND STAMP

  
.....  
potpis

