

CELLULOSIC RETARDER ADDITIVE

KO501.00.0000

PRODUCT DESCRIPTION

KO501 is a cellulosic based retardant additive.

USAGE AREA

It is used in cellulosic based products when ambient weather conditions (humidity exceeds 70% or in extremely hot weather) cause problems (bubbles,bleaching,pinholes) on the surface of the film.

PRODUCT SPECIFICATIONS

Specific Gravity (25°C, kg/l) : 0.905 ± 0.03



Read the technical data sheet



Stir

CONSUMPTION

It can be used 2-5 % on total product.

STORAGE

Store in a cool, dry place and away from heat.

Close all containers after use.

Shelf life is 1 years if stored under specified conditions.

WARNING

Products are recommended for use under temperature conditions 10-32°C for surface, product and environment. Relative humidity should be between 45-65 % during application and drying time. Low temperatures, poor air circulation or high humidity will extend dry times and they also can affect product performance negatively.

HEALTH & SAFETY

For full Health and Safety information please refer to Safety Data Sheet.

Gloves and suitable protective equipment must be worn while using these products.

Good ventilation must be provided in the working environment

It is flammable and inflammable. No smoking during use and should be applied away from heat, fire and sparking devices

TRANSPORT INFORMATION

Freight Classification : Additive

Packaging : **KO501.00**

0,85 kg

3 kg

12 kg

Data provided on this Technical Data Sheet correspond to our best knowledge and experience. We assure consistency on the chemical-physical characteristics of our products, within the tolerance limits specified on our Technical Data Sheets. Responsibility of final result of product application is fully up to the users, who shall make sure that the product corresponds to their own needs with regard to application system, to substrates used as well as to working conditions.

Publish Date:

Revision No:

www.gencboya.com.tr