

**TECHNICAL DATA SHEET**REV. 0  
DATE 18/06/2016**PRODUCT**

(A PART)

**DILUENTE POLIURETANICO K 129 CT****TECHNICAL  
DESCRIPTION**

SOLVENT MIX

**SPECIFICATION AND CHARACTERISTICS** This thinner has a wide solvent range, with a medium quickness evaporation. Universal, suitable for polyurethane base and top-coats systems.**RECOMMENDED USE** Add to polyurethane mixes to reduce viscosity**CHEMICAL-PHYSICAL CHARACTERISTICS (IST-Q-12/02)**

<b>ASPECT / PHYSICAL STATE</b>	colour	colourless
<b>SPECIFIC WEIGHT (A PART)</b>	kg/lt	+/- 0.02 0.87

**SHELF LIFE** 12 months at 20°C in original pack.**SAFETY ADVICES** See information in the safety data sheet.**GENERAL NOTES**

responsibility of final results of coating system rests entirely with the users who shall make sure that product is in compliance with requirement of substrates used and working conditions

**Kemichal S.r.l. – Via Dell’artigianato, 2 – Trebaseleghe (Padova) Italy**  
Telephone 0499385648 – Fax 0499385070 – info@kemichal.it – www.kemichal.itCOMPANY WITH  
QUALITY MANAGEMENT SYSTEM  
UNI EN ISO 9001:2008  
CERTIFICATED  
BY CERTIQUALITY N.4739