

**TECHNICAL DATA SHEET**REV. 1
DATE 09/01/2019**PRODUCT**

(A PART)

DILUENTE POLIURETANICO K 129 CE**TECHNICAL
DESCRIPTION**

POLYURETHANE THINNER

**SPECIFICATION AND
CHARACTERISTICS**

This thinner has an optimum solvent power, with a slow evaporation. Suitable for diluting polyurethane glossy topcoats in standard conditions, polyurethane topcoats and primers in high humidity conditions and/or summer periods.

RECOMMENDED USE Add to polyurethane mix.**CHEMICAL-PHYSICAL CHARACTERISTICS (IST-Q-12/02)**

ASPECT / PHYSICAL STATE	colour	colourless
SPECIFIC WEIGHT (A PART)	kg/lt	+/- 0.02 0.88

SHELF LIFE 12 months at 20°C in original pack.**SAFETY ADVICES** See information in the safety data sheet.**GENERAL NOTES** Recommended preliminary tests.

responsibility of final results of coating system rests entirely with the users who shall make sure that product is in compliance with requirement of substrates used and working conditions



Kemical S.r.l. – Via Dell’artigianato, 2 – Trebaseleghe (Padova) Italy
Telephone 0499385648 – Fax 0499385070 – info@kemical.it – www.kemical.it

COMPANY WITH
QUALITY MANAGEMENT SYSTEM
UNI EN ISO 9001:2008
CERTIFICATED
BY CERTIQUALITY N.4739