

HIGH SOLID HARDENER**993.MS..****Z 37**SCHEDA TECNICA
EDIZ. 10-2002

High solid hardener for Acrylic, Polyurethan Enamel, and Two Coat Transparent.

Completely no yellowing offers very good hardness and resistance to chemicals and atmospheric agents.





















Do not use when the relative humidity is above 80 %.

The methods of use are the following.

ENAMEL	MIX RATIO IN VOLUME			FORD VISCOSITY	STICK
	ENAMEL	HARDENER	THINNER		
		993.MS	075	4	
807 ACRYL. POLYURETH.	100	50	20	18''	2:1
907 MULTI. 2K PASTEL	100	50	30	17''	2:1
910 MULTI.S.T. PASTEL H.S.	100	50	0	18''	2:1
923.MS.. TRANSP.	100	50	15	17''	2:1
923.HS90 TRANSP.H.S.	100	50	25	16''	2:1
823.2011 TRANSP. READY TO USE	100	50	-	17''	2:1
923.2011	100	50	-	18''	2:1
923.ST95 TRANSP. READY TO USE H.S.	100	50	-	18''	2:1

N.B. The dilution percentages are indicative and may vary, even though only slightly depending on the colour.
In every case check the viscosity before spray application.

HIGH SOLID HARDENER
993.MS..

	Natura del prodotto Nature of product Produktbasis Nature du Produit			Spessore film secco Dry film thickness Trockenschichtstarke Epaisseur du film sec	
	Aspetto Appearance Aussehen Aspect			Appassimento Flash time Abluftzeit Dessèchement	
	Colore Colour Farbe Couleur			Fuori polvere (20° C) Dustfree Staubtrocknen Hors poussière	
	Viscosità vendita Selling viscosity Verkaufviskosität Viscosité de vente			Secco al tatto (20° C) Touch free Berührungstrocknen Sec au toucher	
	Peso specifico Specific gravity Spezifisches gewicht Poids spécifique	0.995		Pronto al montaggio Dry to assemble Montage fertig Dur pour assemblage	
	Rapporto miscela Mixing ratio Mischverhältnis Proportion de melange			Essic. Completa Throigh drying 20°C Durckgetrocknet 60°C Sec en profondeur	
 	Prodotto - Product Produkt - Produkt Catalizzatore - Hardener Harter - Catalyseur Diluyente - Thinner Verdunner - Diluant		  	Sopraverniciabile Next coat wet-on-wet Überlackierbar Recouvrable Cart manuale bagnato Sanding by hand wet Schleifenman.nass Papier abrasif à l'eau Cart. Manuale secco Sanding by hand dry Schleifenman. Trocken Papier abrasif sec	
	Pot - life (20° C) Topfzeit (20° C) Vie en pot (20° C)			Roto orbitale bagnato Flat bed sander wet Schleifenmask.nass Orbital mouille	
	Viscosità applicazione Spraying viscosity Verarbeit viscositat Viscosité d'application			Roto orbitale secco Flat bed sander dry Schleifenmask.troc Orbital sec	
	Tazza a caduta Gravity feed spray gun Fließbecher Projecteur - buse			Lucidatura Polishing Polierung Polissage	
	Tazza ad aspirazione Suction feed spray gun Saugbecher Projecteur - buse			Resa mq/kg Yield Ergiebigkeit Rendement	
	Pressione aria (bar) Air pressure Luftdruck (bar) Pression d'application			Prodotti Complementari Subsidiary products	
	Numero mani Number of coats Spritzegange Nombre des couches			Komplementar Produkte Produits Complementaires	
	Applicazione Spatola Application of putty Auftragung spachtel Application a spatule			Conservabilità Ageing Haltbarkeit Conservabilité	1 year in cool and dry place

I dati forniti su questa scheda sono il frutto della nostra migliore esperienza. Tuttavia devono essere considerati quali informazioni senza alcun valore vincolante, anche per quanto riguarda eventuali diritti di proprietà di terzi e non esime il cliente da eseguire propri controlli dei prodotti da noi forniti allo scopo di stimare l'idoneità o meno ai procedimenti ed ai cicli previsti. L'applicazione e l'impiego dei prodotti avvengono

fuori dalle nostre possibilità di controllo e ricadono pertanto sotto l'esclusiva responsabilità del cliente. Nel caso venga chiesta una responsabilità, questa sarà limitata per i danni, al valore dei prodotti da noi forniti e impiegati dal cliente. Ovviamente noi garantiamo una costanza di qualità ineccepibile dei nostri prodotti.