

NOSTALGIE BASE

NOSTALGIE BASE is an acrylic-based emulsion; a fibre-reinforced decorative interior paint.

FEATURES

- Provides a modern look on the applied environments with its sparkling surface
- Due its high vapor permeability, it allows surface to discharge the steam and breathe.
- During application it covers up the faults on the surface with the thick layer of film that forms.
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odour in the application environments with its perfumed feature.

APPLICATION AREA

It is used with a suitable primer after the surface preparation on the walls, plasters, exposed concretes and wooden surfaces in the buildings' interiors.

SURFACE PREPARATION

After cleaning all kinds of dirt, oil, swollen paint and dust on the surfaces to be applied, the surface defects should be corrected by **SAN DECO Acrylic Putty Interior** and primered by **SAN DECO Decoprimer**.

APPLICATION INSTRUCTIONS

- Before the application, NOSTALGIE BASE should be properly mixed without thinning
- NOSTALGIE BASE should be applied irregularly on the surface with a plastic or a steel trowel, according to the desired effect
- Two days after having applied **NOSTALGIE BASE**, apply **NOSTALGIE FINISH** on the surface with circular movements with its special cloth or gloves.
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

TECHNICAL DATA

DENSITY (g/cm³)	1,22±0,02
VISCOSITY (Krebs Unit)	Viscous
FLASH POINT	Water based
PH	8-9
SOLID CONTENT % wt	43±2
VOC (g/lt) (EU Directive 2004/42/EC) Calculated theoretically.	2
DILUTION	No
COLOR	White
THEORETICAL CONSUMPTION * (g/m²) (For one coat)	1000 - 1175
COVERING CAPACITY (m²/kg)	0,8 - 1,0
DRYING TIME (at 23°C)	Touch dry time 5-6 hours, Complete dry time 48 hours
SHELF LIFE**	1 Year
PACKAGING	10 Kg

- * Theoretical Consumption Values are calculated for a single coat application with the condition of the surface smoothness, its porosity and application methods.
- ** Shelf life is valid when the product is stored in its sealed package at cool and dry place, protected from direct sunlight and at stroge temperature + 5°C and + 35°C conditions.

WARNINGS/ PRECAUTIONS

- P 102 Keep out of reach of children.
- P 301* P 310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
- Don't use the containers for food preservation.

