

23410200 BIOSISTEM SPRAY sanitising detergent for walls



Spray product particularly suitable for sanitising walls, joints and tiled surfaces in bathrooms, showers, cellars and basements. Cleans and bleaches any blackened area.



Date of revision	04/03/2019
Composition	Solution with high active chlorine content.
Main properties	<ul style="list-style-type: none">• eliminates stains from walls• easy to apply• prevents the formation of moulds
Applications	For interior and exterior walls. It can be applied on any wall surface. It can be also applied on existing paints and plastic coatings.

Technical specifications (at 20°C, 65% RH)	Reference	Unit	Value
Specific weight (pycnometer)	C022		1.000 ± 0.050
pH	C030		11.5 ± 0.5
Ford viscosity cup no. 4	C042		12.0 ± 1.0

Use	
. Surface and application conditions	Ambient temperature min +5°C / max +35°C RH < 80% Surface temperature min +5°C / max +35°C RH < 10%
. Application method	Roller, brush
. Thinner	Water.
. Dilution	Ready for use
. Theoretical coverage	9-11 sq.m/l for each coat, depending on the absorbency of the surface.

Application cycle

NEW SURFACES OR PREVIOUSLY PAINTED WITH WATERBORNE PAINT.

Treat the surface with 23410200 Biosistem Spray, from a distance of 10 - 15 cm. Wait for the surface to absorb the product for 2 - 3 hours, then clean the treated surface with water. If the result obtained is partial, repeat the operation. After 24 hours from the application, brush the surfaces if necessary.

For a better preventive action, treat the surface with 23410230 Biosistem Titansan; in this case wait at least 24 hours after the application of 23410200 Biosistem Spray.

Apply 23410230 Biosistem Titansan exclusively with a roller or brush, leave to act for 24 - 48 hours, keeping the rooms ventilated. The treatment can be repeated several times for a better penetration into the surface and therefore for best effectiveness.

Complete the painting cycle with 23400250 Fissativo Biosistem fixative (if needed) and with one of the waterborne paints of the Biosistem Line.

Old tempera or lime-based paint must be removed completely.

Notes

We recommend using a brush for an optimal application, because it ensures the maximum penetration into the surface.

Brushes and application tools can be cleaned easily if washed straight away with water.

Any hardened drips can be easily removed with Diluente Nitro 92100012 thinner.

Storage

Do not allow to freeze; store at + 5°C to + 20°C. Once opened, the undiluted product can be kept for 3 months in the closed container and in the dark.

Warnings

During application, you must use PVC or PE protective gloves and goggles.

Ventilate the rooms during application.

Wash brushes and tools immediately after use; do not dump the wash water on the ground or into groundwater.

Keep out of reach of children.

Further information is given in the safety data sheet.

VOC classification - Directive 2004/42/EC - Italian Legislative Decree 161/2006

This product is not regulated.

Specification

Application of 23410200 BIOSISTEM SPRAY, sanitising detergent for walls, for the treatment of blackened surfaces. Ideal for cleaning walls before the application of paint

This information is the result of our practical experience but is purely indicative. For more detailed information, please contact our technical support service. This sheet cancels and substitutes any earlier editions.
