

**TIXE srl**  
Via Carlo Ferrari, 49  
(Frazione Pratalborato)  
15060 Capriata d'Orba (AL) IT  
Phone +39 0143 46397



    
[www.tixepaint.com](http://www.tixepaint.com)  
mail@tixepaint.com  
Partita IVA IT 01779800992



**Famiglia : GOLD PAINT**

## **Product : GOLD PAINT FOR OUTDOOR**

<b>DESCRIPTION</b>	paint, pigmented with bronze powders in different shades.
<b>KEY FEATURES</b>	<ul style="list-style-type: none"><li>- High gloss</li><li>- Large decorative</li><li>- Resists weathering</li></ul>
<b>EMPLOYMENT</b>	<p>Metal (iron / alloys and galvanized steel), wood, masonry, plastics (except PE and PPE). Ideal for the decoration of monumental deleted, railings and architectural elements typically exposed to the weather. The specularity of the metal, it contains, and the resulting gloss, make this a unique product for the decoration of items is subject to repetitive contact with that most difficult weather conditions so embellishing objects and environments.</p>
<b>APPLICATION</b>	<p>The surface to be coated with GOLD PAINT FOR OUTDOOR must be prepared with appropriate treatment, namely:</p> <p><b>ON NEW MEDIA:</b> For a better anchorage and greater length in time, the area must be thoroughly defatted with water and soap or diluter wash. Sand and apply one or more hands of product distance minimum of 12 hours of each other interspersed by a light sanding. Applying a background preparation and apply one or more hands of the product.</p> <p><b>MEDIA ALREADY ON 'Paint:</b> if the existing layer of paint does not recommendations to the complete removal, degreasing with water and detergent and rinse. If the existing paint is in the process of posting brushing and sanding to the bottom these parts, or to paint stripping with paint strippers. Wash with diluent by washing with water or soap and then apply a fund preparation and then apply one or more of the product hands interspersed by light sanding.</p> <p>Use the following funds preparation: For iron, wood, plastic, plaster TIXE CLASSIC PRIMER</p> <p>Recommended applications: a brush, roller, dipping, spraying, airless.</p> <p>Conditions and media: The support must be dry, dust-free and grease and any other substance pollutant Temperature: min. 10 ° C / max 35 ° C Relative humidity of &lt;75% Temperature of medium: min. 10 ° C / max 35 ° C</p>
<b>DILUTION</b>	<p>The product is to be used as such.</p> <p>Given the nature of the pigment, consisting of bronze flakes, there is a strong tendency of the metallic pigment to settle.</p> <p>It is therefore recommended that a thorough mixing of the product before and during</p>

**TIXE srl**  
Via Carlo Ferrari, 49  
(Frazione Pratalborato)  
15060 Capriata d'Orba (AL) IT  
Phone +39 0143 46397



[www.tixepaint.com](http://www.tixepaint.com)  
mail@tixepaint.com  
Partita IVA IT 01779800992



application, so as to ensure the continued consistency of the product.

#### **STORAGE**

In a cool and well ventilated.  
Keep the jar tightly closed, upside down and away from frost and heat.

#### **PHYSICAL CHARACTERISTICS (at 20 ° C and 50% - 60% RH)**

1.30 Kg / Lt. for pale, rich, ± Specific Gravity 0:02 Rich pale, copper

Yield (\*) 8-10 Mq / Kg roller and brush  
10-12 Mq / Kg spray

3 " Cup 2 ISO ± Time of outflow 35

1 hours drying off mark  
5 hours in depth

Colours : RICH PALE AND NATURAL COPPER.

Storage life of at least 36 months

(\*) The yield depends on the nature and porosity of the surface.

#### **VOC CLASSIFICATION**

Paint finishes and cladding for interior / exterior wood, metal or plastic.  
VOC expressed as grams per liter of product ready for use:  
Maximum: 150.00 (2007) - 130,00 (2010)  
Product VOC: 94.62

#### **PRECAUTIONS**

In addition to reports of the risk and precautions governing GILDING FOR EXTERNAL in the form of production and which are listed on the container, you should, before making the application of the product, see its data sheet.  
It 'still a good idea to use gloves and goggles, and make the application in a well ventilated.