

TECHNICAL DATA SHEET

RUBBER PROTEX



RUBBER PROTEX is a one component product intended for ensuring durable protection of a car chassis against corrosion, to be used with a spray gun RANAL. This product is based on bitumen and waxes, and characterized by excellent sound insulation properties. Dried surface is characterized by very good adhesion and in various weather conditions ensures protection against damages caused by small stones or gravel. It is resistant to temperatures between -25 and 80°C.

FOR PROFESSIONAL USE!

IT CAN BE USED ON THE FOLLOWING GROUND TYPES

- ◆ Old paint coats including thermoplastic paints
- ◆ Polyester putties
- ◆ Steel
- ◆ Aluminium
- ◆ Galvanized steel
- ◆ Stainless steel
- ◆ Plastics
- ◆ Polyester laminates
- ◆ Two – component acrylic fillers
- ◆ Epoxy primers

INSTRUCTION FOR USE

The surface to be covered has to be clean, degreased, dry, and free from dust and corrosion.


Shake the container before use!

This product should be applied on a car chassis with a spray gun RANAL with adequate end from the distance of about 30 cm. Working pressure is 3-4 bar. This product can be applied also with a brush. If thin coats are needed, it is recommended to dry previous coat. Clean stained surfaces and tools with solvents.

COLOUR


Black.

EVAPORATION TIME



10-15 minutes

TECHNICAL DATA SHEET**DRYING TIME**



Touch dry*: 120 -180 minutes for 600 µm of wet coat

Completely dry*: 4 – 6 hours for 600 µm of wet coat

CONTENT OF VOLATILE ORGANIC COMPOUNDS

VOC II/B/e limit = 840g/l VOC effective = 378,2 g/l

THEORETICAL EFFICIENCY

For wet coat 600 µm thick the use is 0,6kg/ m².**TOOLS CLEANING**

White spirit RANAL or thinner NITRO RANAL.

STORAGE CONDITIONS

Store in a dark and dry place away from sources of fire and heat. The shelf life in original package at the temperature 20°C is 24 months.

HEALTH AND SAFETY RECOMMENDATIONS

According to Safety Data Sheet of Dangerous Substance for particular product.

PACKAGING

Art. No	Capacity,	Package, pieces:	Package weight, kg:
20201	1L	12	10,00
20202	1,8L	6	12,10
20203	5L	1	5,20
20206	1kg	12	13,99

This information is based on careful, laboratory research and our long-standing experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.