

SECTION 1: SUBSTANCE/MIXTURE IDENTIFICATION AND MANUFACTURER/SUPPLIER IDENTIFICATION

1.1. Product identification

POLYURETHANE SEALANT PU UK

1.2. Relevant identified uses of the substance or mixture and uses advised against

One-component elastic adhesive/sealant particularly suitable for automotive.

SEALANTS AND ADHESIVES FORMULATIONS IN INDUSTRY

Industrial:

SU: 10

ERC: 2.

PROC: 3, 4, 5, 8a, 8b, 9.

PC: 1.

INDUSTRIAL APPLICATIONS OF SEALANTS AND ADHESIVES

Industrial:

SU: 17, 19.

ERC: 5, 8b.

PROC: 10, 8a, 8b.

PC: 1.

Professional:

SU: 17, 19.

ERC: 5, 8b.

PROC: 10, 8a, 8b.

PC: 1.

CHEMICAL SUBSTANCE USE IN LABORATORY

INDUSTRIAL:

PROC: 15.

PC: 1, 21.

1.3. Data of the safety data sheet supplier

Przedsiębiorstwo RANAL Sp. z o.o.

Ul. Łódzka 3

42-240 Rudniki k. Częstochowy, PL

Phone: +48 34 329 45 03

Fax: +48 34 320-12-16

Register number: 000029202

Person responsible for the safety data sheet

ranal@ranal.pl

1.4. Emergency telephone

Tel: +48 34 329 45 03 (from 8.00am till 03.00pm)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication: Respiratory sensitization, category 1

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2. Label elements:

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

POLYURETHANE SEALANT PU UK

Hazard pictograms:

Warning word: **Danger**.

Risk index:

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

EUH204 Contains isocyanates. May produce an allergic reaction.

Precautionary statements:

P284 [In case of inadequate ventilation] wear respiratory protection.

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P342+P311 If experiencing respiratory symptoms: call a POISON CENTER / doctor / . . .

Contains:

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**3.1. Substances**

Information not relevant.

3.2. Mixtures

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP)
REACTIVE MIXTURE OF ETHYLBENZENE, m-XYLENE AND p-XYLENE		
CAS. EC. 905-562-9 INDEX. Reg. no. 01-2119555267-33	0 - 8,3	Flam. Liq. 2 H225, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335
XYLENE (BENZENE <0.01%)		
CAS. 1330-20-7 EC. 215-535-7 INDEX. 601-022-00-9 Reg. no. 01-2119488216-32-XXXX	0 - 8,3	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Note C
ETHYL ACETATE		
CAS. 141-78-6 EC. 205-500-4 INDEX. 607-022-00-5 Reg. no. 01-2119475103-46	1 - 1,5	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.		
CAS. 9016-87-9 EC. INDEX.	0,8 - 0,9	Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317
DIPHENYLMETHANE-4,4'-DIISOCYANATE		
CAS. 101-68-8 EC. 202-966-0 INDEX. 615-005-00-9 Reg. no. 01-2119457014-47-XXXX	0,6 - 0,7	Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin Sens. 1 H317, Note 2 C
PHOSPHORIC ACID		
CAS. 7664-38-2 EC. 231-633-2 INDEX. 015-011-00-6 Reg. no. 01-2119485924-24	0 - 0,05	Skin Corr. 1B H314, Note B

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The two substances with no. REACH: 01-2119555267-33 and Nr. REACH: 01-2119488216-32 constitute a mixture in variable proportions and then the maximum percentage to be considered in the finished product is equal to the maximum considered for only one of them. They having the same classification, each combination does not involve changes in the final classification of the mixture.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms both acute and delayed

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indications of any immediate medical attention and special treatment needed

Information not available.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency measures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

POLYURETHANE SEALANT PU UK

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and materials for containment and cleaning up.

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7.

Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7: HANDLING AND STORAGE OF SUBSTANCES AND MIXTURES**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 10

7.3. Special end use(s)

Information not available.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION MEASURES**8.1. Control parameters**

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España
2015 FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
HRV	Hrvatska	NN13/09 - Ministarstvo gospodarstva, rada i poduzetništva
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Databank of the social and Economic Concil of Netherlands (SER) Values, AF 2011:18
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
SWE	Sverige	Occupational Exposure Limit Values, AF 2011:18
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

XYLENE (BENZENE <0.01%)

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		SKIN.
		mg/m ³	ppm	mg/m ³	ppm	
AGW	DEU	440	100	880	200	

POLYURETHANE SEALANT PU UK

MAK	DEU	440	100	880	200	SKIN.
VLA	ESP	221	50	442	100	SKIN.
VLEP	FRA	221	50	442	100	SKIN.
WEL	GBR	220	50	441	100	
TLV	GRC	435	100	650	150	
GVI	HRV	221	50	442	100	SKIN.
TLV	ITA	221	50	442	100	SKIN.
OEL	NLD	210	442			SKIN.
NDS	POL	100				
MAK	SWE	221	50	442	100	SKIN.
OEL	EU	221	50	442	100	SKIN.
TLV-ACGIH		434	100	651	150	

Predicted no-effect concentration – PNEC:

Normal value in fresh water	0,327 mg/l
Normal value in marine water	0,327 mg/l
Normal value for fresh water sediment	12,46 mg/kg
Normal value for marine water sediment	12,46 mg/kg
Normal value for water, intermittent release	0,327 mg/l
Normal value of STP microorganisms	6,58 mg/l
Normal value for the terrestrial compartment	2,31 mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg/d				
Inhalation			VND	14,8 mg/m ³	289 mg/kg	VND	VND	77 mg/m ³
Skin			VND	108 mg/kg/d			VND	180 mg/kg/d

REACTIVE MIXTURE OF ETHYLBENZENE, m-XYLENE AND p-XYLENE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
TLV-ACGIH		221	50	442	100

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,327 mg/l
Normal value in marine water	0,327 mg/l
Normal value for fresh water sediment	12,46 mg/kg
Normal value for marine water sediment	12,46 mg/kg
Normal value for water, intermittent release	0,327 mg/l
Normal value of STP microorganisms	6,58 mg/l
Normal value for the terrestrial compartment	2,31 mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	1,6 mg/kg				
Inhalation	VND	174 mg/m ³	VND	14,8 mg/m ³	VND	289 mg/m ³	VND	77 mg/m ³
Skin			VND	108 mg/kg			VND	180 mg/kg

ETHYL ACETATE

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min	
		mg/m ³	ppm	mg/m ³	ppm
AGW	DEU	1500	400	3000	800
MAK	DEU	1500	400	3000	800
VLA	ESP	1460	400		
VLEP	FRA	1400	400		
WEL	GBR		200		400
TLV	GRC	1400	400		

POLYURETHANE SEALANT PU UK

GVI	HRV		200		400
OEL	NLD	550		1100	
NDS	POL	200		600	
MAK	SWE	500	150	1100	300
TLV-ACGIH		1441	400		

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,26 mg/l
Normal value in marine water	0,026 mg/l
Normal value for fresh water sediment	1,25 mg/kg
Normal value for marine water sediment	0,125 mg/kg
Normal value for water, intermittent release	1,65 mg/l
Normal value of STP microorganisms	650 mg/l
Normal value for the terrestrial compartment	0,24 mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	4,5 mg/kg				
Inhalation	734 mg/m3	734 mg/m3	367mg/m3	367 mg/m3	1468 mg/m3	1468 mg/m3	734 mg/m3	734 mg/m3
Skin			VND	37 mg/kg			VND	63 mg/kg

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES

Threshold Limit Value.

Type	Country	TWA/8h mg/m ³	ppm	STEL/15min mg/m ³	ppm
OEL	ITA		0,005		
TLV-ACGIH			0,005		

DIPHENYLMETHANE-4,4'-DIISOCYANATE

Threshold Limit Value.

Type	Country	TWA/8h mg/m ³	ppm	STEL/15min mg/m ³	ppm
AGW	DEU	0,05		0,05	
MAK	DEU	0,05		0,05	SKIN.
MAK	DEU	0,05		0,05	INHAL.
VLA	ESP	0,052	0,005		
VLEP	FRA	0,1	0,01	0,2	0,02
TLV	GRC	0,2		0,2	
NDS	POL	0,05		0,2	
MAK	SWE	0,03	0,002	0,05 (C)	0,005 (C)
TLV-ACGIH		0,051	0,005		

Predicted no-effect concentration - PNEC

Normal value in fresh water	1,01 mg/l
Normal value in marine water	0,11 mg/l
Normal value of STP microorganisms	1,01 mg/l
Normal value for the terrestrial compartment	1,01 mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral	VND	20 mg/kg bw/d						
Inhalation	0,05mg/m ³	0,05 mg/m ³	0,025 mg/m ³	0,025 mg/m ³	0,1 mg/m ³	0,1 mg/m ³	0,05 mg/m ³	0,05 mg/m ³
Skin	17,2 mg/cm ²	25 mg/kg bw/d			28,7 mg/cm ²	50 mg/kg/d		

2,2 - DIMORPHOLINODIETHYL ETHER

Predicted no-effect concentration - PNEC.

Normal value in fresh water	0,1 mg/l
Normal value in marine water	0,01 mg/l

POLYURETHANE SEALANT PU UK

Normal value for fresh water sediment	8,2 mg/kg
Normal value for marine water sediment	0,82 mg/kg
Normal value for water, intermittent release	1 mg/l
Normal value of STP microorganisms	100 mg/l
Normal value for the terrestrial compartment	1,58 mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	0,5 mg/kg/d				
Inhalation			VND	1,8 mg/m ³			VND	7,28 mg/m ³
Skin			VND	0,5 mg/kg/d			VND	1 mg/kg/d

PHOSPHORIC ACID

Threshold Limit Value.

Type	Country	TWA/8h		STEL/15min		
		mg/m ³	ppm	mg/m ³	ppm	
AGW	DEU	2		4		INHAL.
MAK	DEU	2		4		
VLA	ESP	1		2		
VLEP	FRA	1	0,2	2	0,5	
WEL	GBR	1		2		
TLV	GRC	1		3		
GVI	HRV	1		2		
TLV	ITA	1		2		
OEL	NLD	1		2		
NDS	POL	1		2		
MAK	SWE	1		3		
OEL	EU	1		2		
TLV-ACGIH		1		3		

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.
 VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified.

8.2. Exposure control

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect your hands with work gloves, category III (ref. standard EN 374). For the final choice of material you need to assess the type of use. In case of contact for the short term or as protection against splashes, use gloves made of nitrile (0.3mm thickness, permeation time >480 min.). In the event of continued exposure use butyl rubber gloves (0.4mm thickness, permeation time > 480 min.). Contaminated gloves should be removed.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166). In case of exceeding the threshold value (eg, TLV-TWA) of the substance or one or more of the substances present in the product, it is advisable to wear a mask with filter type A for organic vapors, the class (1, 2 or 3) must be chosen according to the limit concentration of use (1000, 5000 or 10000 ppm) (ref. standard EN 14387).

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Appearance	paste
Colour	various
Odour	typical
Odour threshold.	Not available.
pH.	Not available.
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	Not applicable.
Evaporation rate	Not available.
Flammability (solid, gas)	not flammable
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1,27 Kg/l
Solubility	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	50000 - 110000 cps
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information

VOC (Directive 2010/75/EC) : 9,98 % - 126,75 g/litre.

VOC (volatile carbon) : Not available.

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

PHOSPHORIC ACID: risk of explosion on contact with nitromethane. May react dangerously with alkalis and sodium borohydride.

10.4. Conditions to be avoided

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

PHOSPHORIC ACID: Metals, strong alkalis, aldehydes, sulphides and peroxides.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

PHOSPHORIC ACID: phosphorus oxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Inhalation of this product causes sensitization, which may then give rise to a series of inflammatory episodes, most of all characterized by obstruction and affecting the respiratory system. Sometimes, sensitization phenomena arise together with evident rhinitis and asthma.

Damages to the respiratory system depend on the inhaled quantity, on the product concentration in the working environment and on the exposure time.

This product contains isocyanates. Producer's specifications are as follows: Ready-to-use products containing isocyanates may irritate mucosas, particularly those of the respiratory system, and may give rise to hypersensitivity reactions.

Vapour or aerosol inhalation may lead to sensitization. Please take all the measures used for all solvent-containing products while manipulating isocyanate-containing products. Avoid vapour and aerosol inhalation. People with allergic or asthmatic precedents or subject to respiratory disorders should not handle products containing isocyanates.

This product contains sensitizing substance/s and may cause allergic reactions.

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.

LD50 (Oral)	> 10000 mg/kg Rattus sp.
LD50 (Dermal)	> 9400 mg/kg Oryctolagus sp.
LC50 (Inhalation)	0,31 mg/l/4h Rattus sp.

DIPHENYLMETHANE-4,4'-DIISOCYANATE

LD50 (Oral)	> 2000 mg/kg Rattus sp.
LD50 (Dermal)	> 9400 mg/kg Oryctolagus sp.
LC50 (Inhalation)	2,24 mg/l Rattus sp.

REACTIVE MIXTURE OF ETHYLBENZENE, m-XYLENE AND p-XYLENE

LD50 (Oral)	5627 mg/kg Mus sp.
LD50 (Dermal)	> 5000 ml/kg Oryctolagus sp.
LC50 (Inhalation)	6700 ppm/4h Rattus sp.

PHOSPHORIC ACID

LD50 (Oral)	1530 mg/kg Rattus sp.
LD50 (Dermal)	2740 mg/kg Oryctolagus sp.
LC50 (Inhalation)	> 0,85 mg/l/1h Rattus sp.

ETHYL ACETATE

LD50 (Oral)	5620 mg/kg Rattus sp.
LD50 (Dermal)	> 20000 mg/kg Oryctolagus sp.
LC50 (Inhalation)	1600 mg/kg Oryctolagus sp.

XYLENE (BENZENE <0.01%)

LD50 (Oral)	5627 mg/kg Mus sp.
LD50 (Dermal)	> 5000 mg/kg Oryctolagus sp.
LC50 (Inhalation)	6700 ppm/4h Rattus sp.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.

LC50 - for Fish. > 1000 mg/l/96h Danio rerio
 EC50 - for Algae / Aquatic Plants. > 1640 mg/l/72h Scenedesmus subspicatus
 Chronic NOEC for Crustacea. > 10 mg/l Daphnia magna

DIPHENYLMETHANE-4,4'-DIISOCYANATE

LC50 - for Fish. > 1000 mg/l/96h Danio rerio
 Chronic NOEC for Algae / Aquatic Plants. 1640 mg/l Desmodesmus subspicatus

REACTIVE MIXTURE OF ETHYLBENZENE, m-XYLENE AND p-XYLENE

LC50 - for Fish. 2,6 mg/l/96h Salmo gairdneri
 EC10 for Algae / Aquatic Plants. 1,9 mg/l/72h Selenastrum capricornutum

ETHYL ACETATE

LC50 - for Fish. > 212 mg/l/96h

POLYURETHANE SEALANT PU UK

EC50 - for Crustacea. 260 mg/l/48h Daphnia pulex
XYLENE (BENZENE <0.01%)
LC50 - for Fish. 2,6 mg/l/96h Oncorhynchus mykiss
EC50 - for Algae / Aquatic Plants. 4,36 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Fish. > 1,3 mg/l Oncorhynchus mykiss
Chronic NOEC for Crustacea. 1,57 mg/l Daphnia magna

12.2. Persistence and degradability

DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.

NOT rapidly biodegradable.

PHOSPHORIC ACID

Solubility in water. > 850000 mg/l

Biodegradability: Information not available.

ETHYL ACETATE

Solubility in water. > 10000 mg/l

Rapidly biodegradable.

XYLENE (BENZENE <0.01%)

Rapidly biodegradable.

12.3. Bioaccumulative potential

ETHYL ACETATE

Partition coefficient: n-octanol/water. 0,68

BCF. 30

12.4. Mobility in soil

Information not available.

12.5. Results of PBT and vPvB assesment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other hazardous effects

Information not available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class (es)

Not applicable.

14.4. Packaging group

Not applicable.

14.5. Environmental hazards

Not applicable.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 Convention and the IBC Code

Information not relevant.

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations / legislations specific for the substance or mixture**

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product:

Point. 3

Contained substance:

Point. 56 DIPHENYLMETHANE DIISOCYANATE, ISOMERS AND HOMOLOGUES.

Point. 56 DIPHENYLMETHANE-4,4'-DIISOCYANATE

Reg. no.: 01-2119457014-47-XXXX

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (VwVwS 2005).

WGK 2: Hazard to waters

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16: OTHER INFORMATION**Text of hazard (H) indications mentioned in section 2-3 of the sheet:**

Flam. Liq. 2 Flammable liquid, category 2

Flam. Liq. 3 Flammable liquid, category 3

Carc. 2 Carcinogenicity, category 2

Acute Tox. 4 Acute toxicity, category 4

Asp. Tox. 1 Aspiration hazard, category 1

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Skin Corr. 1B Skin corrosion, category 1B

Eye Irrit. 2 Eye irritation, category 2

Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Resp. Sens. 1 Respiratory sensitization, category 1

Skin Sens. 1 Skin sensitization, category 1

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H351 Suspected of causing cancer.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

POLYURETHANE SEALANT PU UK

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

Use descriptor system:

ERC 2 Formulation of preparations

ERC 5 Industrial use resulting in inclusion into or onto a matrix

ERC 8b Wide dispersive indoor use of reactive substances in open systems

PC 1 Adhesives, sealants

PC 21 Laboratory chemicals

PROC 10 Roller application or brushing

PROC 15 Use as laboratory reagent

PROC 3 Use in closed batch process (synthesis or formulation)

PROC 4 Use in batch and other process (synthesis) where opportunity for exposure arises

PROC 5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC 8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC 9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

SU 10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

SU 17 General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment

SU 19 Building and construction work

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament

9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the

suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health

and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Other data sources:

ECHA European Chemicals Agency

TOXNET Toxicology Data Network

Changes: general update.

Number Material Safety Data Sheet: 1I3T1116V3