

ACRYL FILLER HS 5+1

SECTION 1: SUBSTANCE/MIXTURE IDENTIFICATION AND MANUFACTURER/SUPPLIER IDENTIFICATION

1.1. Product identification

ACRYL FILLER HS 5+1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Acryl filler (component A) to be applied with a spray gun. For professional use in car refinish.

1.3. Data of the safety data sheet supplier

RANAL Sp. z o.o.

ul. Warszawska 36a
42-240 Rudniki k/Częstochowy
Tel: +48 34 329 45 03
Fax:+48 34 320-12-16

Person responsible for the safety data sheet

ranal@ranal.pl

1.4. Emergency telephone

+48 34 322-28-77 (from 8.00 am to 03.00 pm)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

The mixture was classified as dangerous according to current regulations – see section 15.

Classification 1272/2008/EC:

Irritating to skin. (Skin Irrit.2)
Flammable liquid and vapour. (Flam. Liq. 3)

Classification 1999/45/EC:

Harmful product. Harmful by inhalation and in contact with skin. Repeated exposure may cause skin dryness or cracking. Flammable.

2.2. Label elements:

Contains: xylene

Pictograms:



Warning word: **Caution**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours/spray

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection..

P312 Call a doctor if you feel unwell.

2.3. Other hazards

No data.

ACRYL FILLER HS 5+1

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable.

3.2. Mixtures

Product identification

ACRYL FILLER HS 5+1

Xylene

5-15%

EC: 215-535-7

CAS: 1330-20-7

Index no: 601-022-00-9

Registration no: 01-2119539452-40-XXXX

Classification 67/548/EEC:

R10,

Xn; R20/21

Xi; R38

Classification 1272/2008/EC:

Flam. Liq. 3; H226;

Acute Tox. 4; H332

Acute Tox. 4; H312

Skin Irrit.2; H315

Butyl acetate

5-10%

EC: 204-658-1

CAS: 123-86-4

Index no: 607-025-00-1

Registration no: 01-2119485493-29-XXXX

Classification 67/548/EEC:

R10, R66-67

Classification 1272/2008/EC:

Flam. Liq. 3; H226;

STOT SE 3; H336

1-metoxy -2-propanol acetate

5-10%

EC: 203-603-9

CAS: 108-65-6

Index no: 607-195-00-7

Registration no: 01-2119475791-29-XXXX

Classification 67/548/EEC:

R10

Classification 1272/2008/EC:

Flam. Liq. 3; H226;

Full text of the phrases identifying the types of hazard and R phrases provided in section 16.

ACRYL FILLER HS 5+1

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures:

General information:

See section 11 of the Material Safety Data Sheet.

Inhalation:

Take the victim outside to the fresh air, ensure quiet surrounding, in case of no breath ensure artificial respiration. **Call a doctor.**

Skin:

Take off contaminated clothing. Rinse contaminated skin with plenty of lukewarm water for about 15 min. If irritation persists consult a doctor.

Eyes:

Rinse immediately with plenty of water for about 15 min, avoid strong water jet- risk of cornea damage, consult a doctor.

Alimentary tract:

Do not cause vomiting (choking risk). Rinse mouth with water. If conscious, administer 1-2 glasses of warm water. Call a doctor. Person giving first aid should wear medical gloves.

4.2. Most important symptoms both acute and delayed

Vapours may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.

4.3. Indications of any immediate medical attention and special treatment needed

Special measures allowing for specialist and immediate aid should be available in the place of work.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Powder, foam resistant to alcohols, carbon dioxide, water mist.

5.2. Special hazards arising from the substance or mixture

Carbon monoxide and other toxic gases may be generated in case of fire.

5.3. Advice for firefighters

Fire-fighting teams should wear self-contained breathing apparatus and light protective clothing. Cool adjacent tanks by spraying water from a safe distance.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency measures

For persons not being members of aid giving staff:

Remove ignition sources. Ensure sufficient ventilation of the room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Personal safety measures – see section 8 of Material Safety Data Sheet.

For persons being the members of aid giving staff:

Persons giving aid should wear protective clothing made of coated impregnated fabric, protective gloves (viton), tight protective glasses and breathing apparatus: gas mask with A type absorber.

6.2. Environmental precautions

Prevent leakage to the sewage system, surface waters, underground waters and soil.

6.3. Methods and materials for containment and cleaning up.

Stop the leakage (close the liquid inflow, seal), place damaged container in an emergency container, remove the liquid mechanically and place it in an emergency container. In case of large leakage embank the area. In case of small amounts, collect with the use of a binding agent (e.g. mica, diatomaceous earth, sand).

ACRYL FILLER HS 5+1

6.4. Reference to other sections

Personal protection measures – see section 8 of the Material Safety Data Sheet. Disposal considerations – see section 13 of the Material Safety Data Sheet.

SECTION 7: HANDLING AND STORAGE OF SUBSTANCES AND MIXTURES

7.1. Precautions for safe handling

Keep away from heat and sources of ignition. Prevent leakage to the sewage system, surface waters, underground waters and soil. Use only in well ventilated rooms. Do not smoke. Do not inhale vapours. Avoid contact with skin and eyes. Take precaution measures against electrostatic discharge. Use personal protection measures – see section 8 of the Material Safety Data Sheet.

7.2. Conditions for safe storage, including any incompatibilities

Store in well sealed original containers. Do not store near large amounts of organic peroxides or other strong oxidants. Take precaution measures against electrostatic discharge. Store in cool, well ventilated rooms. Protect from the sunrays, heat sources and low temperatures.

7.3. Szczególne zastosowanie(-a) końcowe

Acryl filler (component A) to be applied with a spray gun. For professional use in car body refinish taking into consideration the information included in subsections 7.1 and 7.2.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION MEASURES

8.1. Control parameters

CAS NUMBER:	SUBSTANCE	MPC (mg/m ³)	MPIC (mg/m ³)	MPCC (mg/m ³)
1330-20-7	Xylene	100	---	---
123-86-4	Butyl acetate	200	950	---
108-65-6	1-metoxy -2-propanol acetate	260	520	---

National acceptable biological values:

CAS NUMBER 1330-20-7
SUBSTANCE ABSORBED Xylene
SUBSTANCE MARKED methyl hippuric acid
BIOLOGICAL MATERIAL urine*
PCB VALUES 0,75 g/g creatinine

Notice: * single sample, taken at the end of a daily exposure any day

8.2. Exposure control

Respiratory tract protection:
Gas mask with A type absorber (EN 141).

Hand protection:
Protective gloves PN-EN 374-3 (viton, 0,7 mm thick, penetration time > 480 min, nitril rubber, 0,4 mm thick, penetration time > 30 min)

Eye protection:
Tight protective glasses.

Skin protection:
Proper protective clothing (coated, impregnated fabrics).

Workplace:
Fixed fume extraction and general ventilation.

Environmental exposure control:
Prevent leakage to the sewage system, surface waters, underground waters and soil.

ACRYL FILLER HS 5+1

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

liquid

Colour

according to specification

Odour

strong, powerful

Odour treshold

0.9-9 mg/m³ (xylene)

pH

not applicable

Melting /freezing point

not applicable

Boliling point

126-145°C

Flash point

24°C

Autoignition point

about 270-300°C

Breakdown point

not specified

Evaporation rate

not specified

Flammability (solid, gas)

not applicable

Explosion limits

% bottom: 1.1 vol% top: 8.0 vol% (xylene)

Vapour pressure

13 hPa (20°C) (butyl acetate)

Vapour density (with regard to air)

4.0 (butyl acetate)

Density

about 1.6 g/cm³ (20°C)

Solubility (in water)

poor

n-oktanol/water division ratio

1,85 (octan butylu)

Viscosity (rotational rheometer)

5000 – 10000 mPas

Explosive properties

not applicable

Oxidizing properties

not applicable

9.2. Other information

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Product not reactive under normal conditions.

10.2. Chemical stability

Product stabile under normal conditions.

10.3. Possibility of hazardous reactions

Carbon monoxide and other toxic gases may be generated as a result of thermal decomposition.

10.4. Conditions to be avoided

Flammable product. Avoid contact with strong oxidants, peroxides, strong acids and bases. Avoid generation and accumulation of static electricity. Protect from the influence of sunrays and heat sources.

ACRYL FILLER HS 5+1

10.5. Incompatible materials

Avoid contact with large amounts of organic peroxides, strong acids and bases, as well as other strong oxidants.

10.6. Hazardous decomposition products

Carbon monoxide and other toxic gases are generated as a result of thermal decomposition.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No experimental data available on the preparation. Evaluation based on the data on dangerous ingredients included in the preparation.

a) Acute toxicity

Xylene

LD ₅₀ (rat, ingestion)	4300 mg/kg
LC ₅₀ (rat, inhalation)	5000 ppm/4h
LD ₅₀ (rabbit, skin)	1700 mg/kg

Butyl acetate

LD ₅₀ (rat, ingestion)	10768 mg/kg
LC ₅₀ (rat, inhalation)	390 ppm/4h
LD ₅₀ (rabbit, skin)	17600 mg/kg

1-methoxy -2-propanol acetate

LD ₅₀ (rat, ingestion)	8532mg/kg
LD ₅₀ (rabbit, skin)	5000 mg/kg

b) Irritating effect

Skin: irritating to skin and mucous membrane

Eyes: irritating effect

c) Caustic effect

Mixture is not classified as caustic. No available data confirming the hazard class.

d) Allergic effects

Mixture is not classified as allergenic. No available data confirming the hazard class.

e) Toxicity for repeated exposure

Repeated exposure may cause skin dryness or cracking.

f) Cancerogenity

Mixture is not classified as cancerogenic. No available data confirming the hazard class.

g) Mutagenity

Mixture is not classified as mutagenic. No available data confirming the hazard class.

h) Harmful effect on reproduction

Mixture is not classified as harmful to reproduction. No available data confirming the hazard class.

Exposure methods:

Respiratory tract: Harmful in case of inhalation.

Skin: Harmful to skin.

Eyes: Irritating to eyes.

If swallowed the substance may cause irritation of the alimentary tract, nausea, vomiting and diarrhea.

Poisoning symptoms:

Headaches and dizziness, fatigue, decreased muscle power, drowsiness and in exceptional instances loss of consciousness. Vapours may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.

ACRYL FILLER HS 5+1

SECTION 12: ECOLOGICAL INFORMATION

No experimental data available on the preparation. Evaluation based on the data on dangerous ingredients included in the preparation.

12.1. Toxicity

1-metoxy -2-propanol acetate

Daphnia magna EC50 (48 hours) > 500 mg/l

Oncorhynchus mykiss LC50 (96 hours) 100-180 mg/l

Number in catalogue of water hazardous substances: 5033

Water hazard class: 1

Xylene

Daphnia magna EC50 (48 hours) 7,4 mg/l

Acute toxicity for mammals: 3; for fish: 4,1

Number in catalogue of water hazardous substances: 206

Water hazard class: 2

Butyl acetate

Number in catalogue of water hazardous substances: 42

Water hazard class: 1

12.2. Persistence and degradability

Butyl acetate

Biodegradability: 98% (close bottle test)

12.3. Bioaccumulative potential

Butyl acetate

Biodegradation coefficient: BCF=3,1

12.4. Mobility in soil

Very poorly soluble in water.

12.5. Results of PBT and vPvB assesment

No data available.

12.6. Other hazardous effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product must be disposed of in compliance with the proper local and statutory regulations with regard to waste – see point 15.

Product remains:

Waste code: 08 01 11* Do not dispose the product into the sewage system. Do not store with communal waste.

Remove the remains of the mixture carefully and harden with the use of the proper B component, a (waste) hardener from the set. Hardened product is not harmful waste.

CAUTION: harden the remains in small portions away from flammable products. High amounts of heat are released during chemical reaction.

Contaminated container:

A contaminated container containing unhardened remains of the product is harmful waste. Waste code: 15 01

10*. Do not store with communal waste. The contaminated container should be disposed with entities which are authorized to collection, recover o disposal.

SECTION 14: TRANSPORT INFORMATION

14.1. UN number

1263

14.2. UN proper shipping name

PAINT

ACRYL FILLER HS 5+1

14.3. Transport hazard class (es)

3

14.4. Packaging group

III

14.5. Environmental hazards

no

14.6. Special precautions for user

Do not transport together with products of class 1 (except products of class 1.4S), and some products of class 4.1 i 5.2. During the transport avoid direct contact with products of class 5.1 i 5.2. Do not use an open flame and do not smoke.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 Convention and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislations specific for the substance or mixture

- Directive 67/548 /EWG (2006/121/WE)
- Directive 91/155/EWG (2001/58/WE)
- Directive 1999/45/EC (2006/8/WE)
- REACH – Regulation 2006/1907/WE
- CLP – Regulation 1272/2008/WE

15.2. Chemical safety assessment

Not performed

SECTION 16: OTHER INFORMATION

16.1 Full text of the phrases identifying the types of hazards and R phrases mentioned in sections 2-15:

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R38 Irritating to skin.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Flam.Liq.3

H226 Flammable liquid and vapours.

STOT SE 3 Toxic effect on target organs – single exposure, cat. 3

H336 May cause drowsiness or dizziness

Acute Tox. 4

H332 Harmful if inhaled.

H312 Harmful in contact with skin.

Skin Irrit. 2

H315 Causes skin irritation category 2

EUH066 Repeated exposure may cause skin dryness or cracking

Explanations of the abbreviations and acronyms used in the Material Safety Data Sheet:

Nr CAS – numerical symbol ascribed to a chemical substance by the American organization Chemical Abstracts Service (CAS).

Nr EC – a number ascribed to a chemical substance in the European List of Notified Chemical Substances (ELINCS), or a number in the European Inventory of Existing Chemical Substances mentioned in "No-longer polymers" publication (EINECS)

MPC – maximum permissible concentration of health hazardous substances in the work place.

MPIC – maximum permissible instantaneous concentration.

MPCC – maximum permissible ceiling concentration.

ACRYL FILLER HS 5+1

PCB – permissible concentration in biological material

UN number – four-digit identification number of a substance, preparation or product pursuant to UN model regulations

Information based on our current knowledge. This document shall not constitute warranty for product characteristic.

Classification of the mixture is based on classification rules contained in directive 1999/45/EC.

Changes: general update