

TECHNICAL DATA SHEET

Car body protection agent ANTIGRAVITEX spray

Produced on the basis of high quality synthetic resins, designed for protection of car bodies, it is also perfect for underbody protection. Cured coat is elastic, resistant to gravel, stones, salt and weather conditions.

It can be used on the following surfaces:

- Plastics
- Wash primers
- Polyester putties RANAL
- Polyester laminates
- Aluminium
- Steel
- Galvanized steel
- Stainless steel

Content of volatile organic compounds (VOC):

Acceptable (II/B/e) = 840 g/L

For ready to use mixture - 750 g/L

Instruction for use:

Before application clean, dry and degrease the surface. Protect with masking tape all places not designed for coating. Shake the container before use. Apply 2-3 single coats. Between the applications of the coats wait for about 5-10 minutes. After application clean the valve for 5 seconds.

Attention! Do not apply in the temperatures below 10°C.

TECHNICAL DATA SHEET**Curing time:**

40 to 60 minutes in the temperature of 20°C. It can be over coated when definitely cured (60 minutes).

Available colour:

White, black, grey.

Storage conditions:

Store in a dark and cool place away from fire and heat sources. The shelf life in original package in the temperature of 20°C is 60 months.

Health and safety recommendations:

According to Material Safety Data Sheet of Dangerous Substance for particular product.

Packaging:

| Art. No | Capacity | Package, pieces: | Weight of carton, kg: |
|---------|-----------------------|------------------|-----------------------|
| 20111-1 | 500 ml (spray), white | 12 | 7,50 |
| 20131-1 | 500 ml (spray), grey | 12 | 7,50 |
| 20141-1 | 500 ml (spray), black | 12 | 7,50 |

This information is based on careful, laboratory research and our long-standing experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.