

TECHNICAL DATA SHEET**CLEAR COAT
SPRAY**

Quick drying clear coat, characterized by good surface hardness, high efficiency of covering and excellent adhesion. It is resistant to scratches as well as to chemical factors and weather conditions.

FOR PROFESSIONAL USE!**IT CAN BE USED ON THE FOLLOWING GROUND TYPES**

- ◆ Base coats.
- ◆ Matted and degreased old coats in good condition.

PRODUCT CHARACTERISTICS

- ◆ Very thorough covering of the painted surface.
- ◆ High resistance to abrasion and weather conditions.
- ◆ Possible use inside as well as outside.

COLOUR

- ◆ Clear gloss.
- ◆ Clear mat.

INSTRUCTION FOR USE

- ◆ Sand the surface with P600 paper before use.
- ◆ Clean, dry and degrease the surface before application.
- ◆ Shake the container before use.
- ◆ Apply 1-2 single coats from the distance of about 30 cm.
- ◆ Make 5-10 min. pauses between the applications of the coats.
- ◆ Clean the nozzle after use, by putting the container upside down and pressing it for 5 seconds.

ATTENTION! It is best to paint in a dry room at the temperature of 20°C.

DRYING TIME

Dust free: 5÷8 min.
Touch dry: 60 min.
Completely dry: 24 h

TECHNICAL DATA SHEET**THEORETICAL EFFICIENCY**

400 ml of the coat is enough to cover app. 1,0 - 2,0 m² of the surface.

CONTENT OF VOLATILE ORGANIC COMPOUNDS

II/B/e limit = 840 g/l, VOC = 650 g/l

STORAGE CONDITIONS

Store in a dark and dry place away from the sources of fire and heat. The shelf life in original package at the temperature of 20°C is 36 months.

HEALTH AND SAFETY RECOMMENDATIONS

According to Material Safety Data Sheet of Dangerous Substance for particular product.

PACKAGING

Art. No	Capacity, L	Package, pieces:	Package weight, kg:
30103 [gloss]	0,4	12	5,20
30106 [mat]	0,4	12	5,20

This information is based on careful laboratory research and many years of experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.