

# **TECHNICAL DATA SHEET**



# **ML SPRAY**

Anti corrosion wax coating to protect inside spaces of car bodyworks such as insides of doors, side panels, motor hoods and chassis bars etc. Can also be use on sheets of metals, tools and machinery during storage.

### **Properties:**

Non-drying coating on metals with long term corrosion protection. Resistant to salt, moisture and general corrosive atmosphere. Strong penetration so that difficult accessible parts of the bodywork can be conserved. Non aggressive to plastics, rubbers, and paints

# **Technical information:**

Solvents:	Xylene, Esters en ketones.		
Odour:	Typical		
Gloss	Matt: Ca 8 GU 60 degrmeasuring angle		
Density:	Aerosol: 0,66 Active agent 0,80		
Solids:	Aerosol : 16 % Active agent 30%		
Salt spray test DIN50 021	100 mu 500 hours Ri 0 100 mu 1000 hours Ri 1		

# **Drying times:**

100 m $\mu$  wet layer / 20°C and ventilation Dust dry: ca. 1 hours Trough dry : 1 day

### **Application temperature:**

10°C – 25°C

### Instruction for use:

Use on room temperature. Shake before use. Surface must be dry and clean, free from dirt, rust, grease etc. Spray an even layer on the object or surface to be coated.

RANAL Sp. z o.o.		Registry number: 000029202
Tel.: +48 34 329 45 03	Łódzka 3	www.ranal.pl
Fax: +48 34 320 12 16	42-240 Rudniki, PL	ranal@ranal.pl





# **TECHNICAL DATA SHEET**

For the treatment of cavities a special actuator with long tube and around spraying nozzle can be used.

Leave to evaporate/dry.

Do not spray on the exhaust, brake systems, or on motor parts.

After use, to clean the nozzle and prevent blockage, hold the can up side down and spray until only gas (propellant) is coming out of the can

Can be removed with aromatic solvents as white spirit, boiling point naphtha, xylene, etc.

# **Recommended layer thickness:**

100 mµ wet, 30 mµ dry

### Color:

**Brown** - Transparent

### Storage:

To be stored in dry and cool place between the 10°C en 25°C, away from the sources of light and heat. Avoid sun exposure. Storage time of the product in the original, unopened package is 12 months.

# Health and safety recommendations:

Apply safety data sheet of the particular product.

### Packaging:

Art. Nr	Capacity, L:	Package, pieces	
20361-1 (brown)	400 ml	12	
20371-1 (transparent)	400 ml	12	

This information is based on careful, laboratory research and our long-standing experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.

RANAL Sp. z o.o.			
Tel.: +48 34 329 45 03	Warszawska 36a	www.ranal.pl	DANA
Fax: +48 34 320 12 16	42-240 Rudniki, PL	ranal@ranal.pl	

