

BETON DECO

DESCRIPTION

BETON DECO is an acrylic-based emulsion and natural lime added decorative plaster which gives a stylish exposed concrete look.

It is suitable for interior use but there is also exterior version is available.

APPLICATION AREA

It can be applied to rough plaster, concrete, mineral surfaces like cement plate, gypsum board, drywall, fixed plywood and surfaces with old paint of interiors and exteriors.

FEATURES

- It gives an exposed concrete effect
- It is alkali-resistant and has a long- life time.
- Despite its water resistant feature off the surface through product, with its high vapor permeability, it allows surface to breathe
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odour in the application environments with its perfumed feature.

SURFACE PREPARATION

- Clean any dirt, oil, swollen paint and dust on the surface and correct any surface impurities using SAN DECO Acrylic Putty Interior.
- First surfaces should be applied with SAN DECO Decoprimer. It is advised to use the same color of primer with the selected product color.

APPLICATION INSTRUCTIONS

- BETON DECO should be mixed until it is homogenous; if it is needed clean water can be add to attain the application viscosity
- After undercoat is completely dry, BETON DECO should be applied properly to the surface by using trowel as first coat.
- After 5-6 hours later at 23 ° C, second coat application should be done in the same style and smoothed with trowel.
- For different pattern and thickness with BETON DECO, different effects can be applied by trowel.
- The environment of application must be kept between +5 °C to +35 °C within 24 hours during and after the application.

DRYING TIME

Allow 5-6 hours for touch dry and 24-48 hours for complete dry at 23 °C environment conditions.

PACKING

10Kg / 20 Kg

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

-1 lt covers 2,25 – 2,85 m² of surface

-1 kg covers 1,35 – 1,65 m² of surface

-The paint consumption for 1 m² area is 350 – 440 ml and 600 – 750 gr.

STORAGE

It should be stored for 1 year in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5 °C and +35 °C.

HAZARD STATEMENTS

- H318 Causes serious eye damage.

PRECAUTIONARY STATEMENTS

- P 102 Keep away from children.
- P280 Use protective gloves/protective clothing / goggles / face mask.
- P302+P352 IN CASE OF CONTACT WITH THE SKIN: Wash with abundant water and soap.
- P332+P313 In case of Skin Irritation: Seek medical aid/assistance.
- P 301+P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
- P305+P351+P338 IN CASE OF EYE CONTACT: Flush carefully with water for a few minutes. If any, take your contact lenses out. Continue to flush.
- Do not use the containers for food preservation.

Note: For more technical information please review product's materials security information form.