



**ADESIVI RESINE
VERNICI**

LEGNODUR 101

DESCRIPTION

Fast setting vinyl - adhesive for gluing hard and resinous woods, is therefore used in the furniture industry.

TECHNICAL CHARECTERISTICS

Solids content	+ - 50%
MFFT (min. film form. Temp.)	+ 7 C °
Suggested room and working temp.	+ 15 ° C
Appearance of film	Transparent
Open time	5 / 10 '
Medium seal resistance of adhesive	200 kg /scm
Mechanical stability	excellent

APPLICATION

The adhesive LEGNODUR 101 must be used without adding water. Particularly suitable for bonding hard and resinous woods, this important and specific properties is due to a framework of chemical and physical properties of the polymer dispersion that allows for carefully balanced:

- 1) **HIGH BONDING POWER**
- 2) **FAST SETTING**
- 3) **EXCELLENT PENETRATION ON HARDWOODS AND SOFTWOODS**

The latter property means that when an imbalance of the joint is not posted along the line of glue, but exhaust them depth of glued surfaces.

PRECAUTIONS

Keep from freezing store at + 5 °C

PACKAGING

Can	1 kg
Bucket	5 – 10 – 20 Kg
Tank	25 Kg
Drum	120 – 200 Kg
IBC Cont.	1.000 Kg

RECOLL INTERNATIONAL srl guarantees that the information in the present sheet are given to the best of its experience and technical-scientific knowledge; however, it is not liable for results obtained as application conditions are out of its control. It is recommended to always verify the suitability of the product for the specific case. The present sheet annuls and substitutes any previous sheet.

RECOLL INTERNATIONAL s.r.l.
Via Edison 23 Z.I. Anconetta 36063 Marostica (Vi) Italy
Tel. +39 0424 471189 - Fax +39 0424 471196
www.recoll.it - E-mail: recoll@recoll.it PIVA 03412200242