## WAX

## **DESCRIPTION**

WAX is an emulsion based final coat polish for DECOSTUCCO product.

### **APPLICATION AREA**

It is applied on effect paint products like Decostucco to give an appearance of more glossy marble and bright look.

### **FEATURES**

- It increases the brightness of the decorative material applied and provides a glossy marble look,
- It is easy to apply with a steel trowel,
- As it is water-based, it is harmless to human health and environment.

### **SURFACE PREPARATION**

The surface where WAX application will be done should be completely dry; all dust and dirt should be cleaned.

### **APPLICATION INSTRUCTIONS**

- WAX should be applied as two coats with steel trowel without dilution on the surface where DECOSTUCCO application is completed on it. Between each coat, 30 minutes to 1 hour should be allowed at 23 °C,
- The second coat should be polished with velvety cloth before the coat gets dry,
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

## **DRYING TIME**

Allow 30 minutes - 1 hour for touch dry and 24 hours for complete dry at 23 °C environment conditions.

# **PACKAGING**

1 Kg

## THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

- -1 lt covers 25,0-34,0 m<sup>2</sup> of surface,
- -1 kg covers  $25,0 34,0 \text{ m}^2$  of surface,
- -The paint consumption for 1 m<sup>2</sup> area is 30 -40 ml and 30 40 gr.

### **STORAGE**

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; during 1 year and at a temperature between +5 °C and +35 °C.

## **PRECAUTIONARY STATEMENTS**

- P 102 Keep out of reach of children,
- P 301+ P 310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
- Do not use the containers for food preservation.

Note: For more technical information, please check the Material Safety Data Sheet (MSDS) of the product.