

TRAVERTINO

TRAVERTINO is a mineral-based and natural decorative plaster that provides a travertine aspect on the surface of interior walls.

FEATURES

- It enables to create effects with different patterns during the application with applicator's skills
- Due its high vapor permeability, it allows surface to discharge the steam and breathe
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odor in the application environments with its perfumed feature.

APPLICATION AREA

On all the interior walls, plaster, gross concrete and timber surfaces; it is used together with its appropriate primer after the surface preparation.

SURFACE PREPARATION

After removing all kinds of dirt, grease, bloated paint and dust from the surfaces where **TRAVERTINO** will be applied, the surface defects should be corrected **SAN DECO Acrylic Putty Interior** and undercoated with **SAN DECO Decoprimer**.

APPLICATION INSTRUCTIONS

- TRAVERTINO is applied without dilution, with a stainless steel trowel without dilution so that the first layer thickness will be at least of 1mm.
- Wait minimum 6 hours before applying the second layer
- Before the thorough-drying, you can give the effect on the surface with a special sponge
- In order to obtain a proper finish, the surface should be polished with a steel trowel
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

TECHNICAL DATA

DENSITY (g/cm³)	1,76±0,02
VISCOSITY (Krebs Unit)	Viscous
FLASH POINT	Water based
PH	8-9
SOLID CONTENT % wt	77±2
VOC (g/lt) (EU Directive 2004/42/EC) Calculated theoretically.	40
DILUTION	No
COLOR	Travertino Color Chart-It can be colored with "tinting system."
THEORETICAL CONSUMPTION * (g/m²) (For one coat)	750-1000
COVERING CAPACITY (m²/kg)	1,0-1,35
DRYING TIME (at 23°C)	Touch dry time 5-6 hours, Complete dry time 48 hours
SHELF LIFE**	1 Year
PACKAGING	10 Kg / 20 Kg

- * Theoretical Consumption Values are calculated for a single coat application with the condition of the surface smoothness, its porosity and application methods.
- ** Shelf life is valid when the product is stored in its sealed package at cool and dry place, protected from direct sunlight and at stroge temperature + 5°C and + 35°C conditions.

WARNINGS/ PRECAUTIONS

- P 102 Keep out of reach of children.
- P 301+ P 310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
- Don't use the containers for food preservation.

