



## TECNICAL DATA SHEET

**Nitrocellulose paint by RAL - 20-30% gloss**  
**Product code: 12300**

### Product description:

It is a nitrocellulose resin based, one component fast drying, air dried bright, matt economic finish coat.

### General use

Very good results can be obtained in furniture groups, and it is a high performance paint in many metal industry aimed at very serial drying. It exhibits an excellent finish coat property after first working with cellulosic primer.

### Tecnical Specification

Density	: 1,10-1,30 g/ml
Solid %	: Weight : 50-60 : Volume : 35-45
Viscosity	: 300-350 sec
Application viscosity	: 18-22sec (20°C, with airless %40-50 cellulosic thinner)
Gloss	: 20-30

### Drying time

Drying Times 20°C	Dust Dry	Touch Dry	Hard Dry
		5-10 min	10-20 min

### Coverage/ Spreading

Coverage	Dry film	Yet Film	Spreading
Applicable (MICRON)	30-50	50-70	5-8 m <sup>2</sup> /lt
Recommended(MICRON)	40μ	60μ	6 m <sup>2</sup> /lt

### Application

It must be applied by spraying. It should be applied 2-3 times as long as 10-15 minutes between layers. Cellulosic topcoat application can be done after cellulosic primer drying.

**Shelf life** 2 years in unopened package