ATRACTO



ATRACTO is an acrylic emulsion based decorative coating with silky and gold mother-of-pearl finish consisting of metallic pigments

FEATURES

- ATRACTO provides a glittering decorative look by its metallic pigments content
 Rich and bright pigments give a pleasant brightness to the surface.
 - Due its high vapor permeability, it allows surface to discharge the steam and breathe
 - As it is water-based, it is harmless to human health and environment
 - It provides a pleasant odour in the application environments with its perfumed feature.

APPLICATION AREA

On all the interior walls, plaster coating, gross concrete and wooden surfaces; it is used together with its appropriate primer after the surface preparation.

SURFACE / PREPARATION

After removing all kinds of dirt, grease, bloated paint and dust from the application surface, the surface defects should be corrected with **SAN DECO Acrylic Putty Interior** and undercoated with **SAN DECO Decoprimer**.

APPLICATION INSTRUCTIONS

- ATRACTO should be mixed homogenously, without dilution.
- At first coating, **ATRACTO** should be applied by steel trowel.

The second coat can be completed by using a towel again with giving desired effect

• Minimum 6 hours should be allowed between each coat

• The environment of application must be kept between +5 °C to +35 °C within 24 hours during and after the application.

TECHNICAL DATA

| DENSITY (g/cm³) | 1,20±0,02 |
|---|--|
| VISCOSITY (Krebs Unit) | Viscous |
| FLASH POINT | Water based |
| РН | 8-9 |
| SOLID CONTENT % wt | 40±2 |
| VOC (g/lt) (EU Directive 2004/42/EC) Calculated theoretically. | 52 |
| DILUTION | No |
| COLOR | Atracto Color Chart-It can be colored with "tinting system." |
| THEORETICAL CONSUMPTION * (ml/m²) (For one coat) | 80 - 125 |
| COVERING CAPACITY (m²/L) | 8,0 - 12,5 |
| DRYING TIME (at 23°C) | Touch dry time 5-6 hours, Complete dry time 24 hours |
| SHELF LIFE ** | 1 Year |
| PACKAGING | 1 L / 2,5 L |

* Theoretical Consumption Values are calculated for a single coat application with the condition of the surface smoothness, its porosity and application methods.

****** Shelf life is valid when the product is stored in its sealed package at cool and dry place, protected from direct sunlight and at stroge temperature + 5°C and + 35°C conditions.

WARNINGS/ PRECAUTIONS

- P 102 Keep out of reach of children.
- P 301+ P 310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
- Don't use the containers for food preservation.

