

## FEATURES

- **COMETA** is a decorative product for interiors, which hides uneven wall surfaces easily due to its particulate structure and toning effect,
- It is resistant to hard and long-term abrasion,
- As it is water-based, it is harmless to human health and environment,
- It provides a pleasant odor in the application environments with its perfumed feature.

## APPLICATION AREA

Used on wall, plaster coating, concrete and wood surfaces after surface preparation with the appropriate primer.

## SURFACE PREPARATION

- After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with **SAN DECO Acrylic Putty Interior**, and painted surfaces should be primed with **SAN DECO Decoprimer**,
- After Decoprimer is diluted by volume %20-25 with clean water, it should be applied to the surface with a brush with two layers application. In between layers complete dry condition must be provided.

## APPLICATION INSTRUCTIONS

- After primer completely dried, **COMETA** is mixed carefully with a spatula and applied by its special brush. After 25 minutes, the desired final look should be given to the surface with a plastic spatula; different decorative effects can be achieved by the technique used,
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

## TECHNICAL DATA

<b>DENSITY (g/cm<sup>3</sup>)</b>	1,03±0,02
<b>VISCOSITY (Krebs Unit)</b>	105-120
<b>FLASH POINT</b>	Water based
<b>PH</b>	7-7,5
<b>SOLID CONTENT % wt</b>	15±2
<b>VOC (g/lt)</b> (EU Directive 2004/42/EC) Calculated theoretically.	26
<b>DILUTION</b>	No
<b>COLOR</b>	Cometa Color Chart-It can be colored with "tinting system."
<b>THEORETICAL CONSUMPTION * (ml/m<sup>2</sup>)</b> (For one coat)	100 - 130
<b>COVERING CAPACITY (m<sup>2</sup>/L)</b>	7,5 - 9,5
<b>DRYING TIME (at 23°C)</b>	Touch dry time 4-5 hours, Complete dry time 24-48 hours
<b>SHELF LIFE**</b>	6 Months
<b>PACKAGING</b>	2,5 L

\* Theoretical Consumption Values are calculated for a single coat application with the condition of the surface smoothness, its porosity and application methods.

\*\* Shelf life is valid when the product is stored in its sealed package at cool and dry place, protected from direct sunlight and at storage temperature + 5°C and + 35°C conditions.

## WARNINGS/ PRECAUTIONS

- **P 102** Keep out of reach of children.
- **P 301+ P 310 IF SWALLOWED:** Immediately call a **POISON CENTRE** or doctor/physician.
- Don't use the containers for food preservation.