



TECHNICAL DATA SHEET

1K Acrylic UV resistant paint by RAL - 75-85% gloss
Product code: 15720

Definition: Special stiren modified resin based fast drying, glossy topcoat

Properties: Moderately corrosive environments, fast-drying top coat for protection of steel construction and mechanical equipment is used as a paint

Technical Specification

Density : 1,0 -1,20
Solids % : Weight: 55-65
Glossiness : Glossy

Application Method Paint application should be done professionally. Waiting for primer to dry Industrial Primer is applied to the surface. In confined spaces provide adequate ventilation during application and drying. And area of use for a different thicknesses depending on purpose. This will alter spreading rate and waiting time to affect drying time between coats. Are made up of two layers. 5% in airless spray, air spray application of 10%, brush-roll in a 5% diluted with a thinner.

Coverage/ Spreading 1L with 12-14 m² surface can be painted. (30 micron thick)

Drying Time: (25 °C) Touch dry within 15-20 min. and Hard dry after 3-4 hours


Shelf life 2 years in unopened package



CLEAN THE SURFACE



STIR



THIN WITH SPECIAL THINNER



APPLY WITH BRUSH GUN



APPLY WITH ROLLER



STORE IN TIGHTLY CLOSED PACKAGES



Xn: Harmful



F: Flammable



lead-free