

# DECK CLEANER EXTERIOR WOOD CLEANER

DC-120

BO120.00.0000



## Apply with brush

## PRODUCT DESCRIPTION

**Deck Cleaner** is an exterior wood cleaner to be used on wornout wooden surfaces which are free from varnish or paint. It is a quick and effective cleaning solution which can be used to refurbish darkened or green surfaces for a refreshing apperance.

### Ctir

## RECOMMENDED USES

For exterior use on wooden surfaces free from paint and varnish. Can also be used to clean any type of darkened or green wooden surfaces.



## Store in co

## PRODUCT SPECIFICATIONS

Product Type : Water Based Specific Gravity (kg/L) :  $1,00 \pm 0,02$  Cleaning capacity (m<sup>2</sup>/L) : 8 - 10

freezing

## **SURFACE PREPARATION**

The application surface must be free from paint and varnish.

## **APPLICATION**

Product is ready for use. Does not require thinning. Before usage the product must be stirred well to obtain a homogenous mixture.

Pour the product on wooden surface spread with a brush. Wait at least 3 hours then wash the surface with water. With 1 L of product, 8-10 m<sup>2</sup> of surface can be cleaned. (The required amount may vary according to the absorbency of wood, laying pattern and degree of pollution.)

If the surface is extremely dirty and darkened repeat the same process one more time.

Wait 24 hours before any other operation.

## STORAGE & HANDLING

Store in a dry, cool place, keep away from direct sunlight. After use, firmly close the packing caps.

## **HEALTH & SAFETY**

- 1. For full Health and Safety information please refer to Material Safety Data Sheet (MSDS).
- 2. Gloves and suitable protective equipment must be worn while using these products.
- 3. Good ventilation must be provided in the working environment.

### **WARNING**

During application and drying recommended temperature is between 10-32°C and relative humidity must be below 50 %.

## TRANSPORT INFORMATION

Packaging : 5 LT

Data provided on this Technical Data Sheet correspond to our best knowledge and experience. We assure consistency on the chemical- physical characteristics of our products, within the tolerance limits specified on our Technical Data Sheets. Responsibility of final result of product application is fully up to the Users, who shall make sure that the product corresponds to their own needs with regard to application system, to substrates used as well as to working conditions.

Publish Date: 03.2017

Revision No: 00 www.woodsol.com.tr 01