



PRODUCT DESCRIPTION

Acrylic copolymer emulsion-based, white-pigment, thin-layer interior primer.

SPECIFICATIONS

Increases the coating ability of the finishing coat and enables it to better stick on the surface. Thanks to its thin pattern, it creates an ideal surface for water-based paints for which brightness and texture is important, such as Fawori Silicon Silk. It increases the absorption power of the surface and provides savings from paint and time.

APPLICATION SURFACES

Applicable on concrete, exposed concrete, rough-cast surfaces, MDF, precast concrete panels, OSB, brick, self-supporting old-paint (water-solvent based), and surfaces to which putty has been applied.

APPLICATION

Priming is carried out after the application surfaces are cleaned from any kind of molding oil, stains, dust, and loose layers. Dull the surface with sand paper before moving on to a water-based system on synthetic painted surfaces and in Silky-matt - Semi-matt - Glossy water-based systems (before primer application). Hardening periods of cement-based plasters and repair materials must be complied with. Care should be taken to ensure that the surface temperature stays between +5°C and +30°C throughout application. Protect the surface from frost during primer application and drying. Apply as a single coat using a brush, roller, or airless spray. After the application, all used tools should be cleaned with water.

Note: Apply using a wide transparent sealing tape on newly plastered surfaces. Apply the primer only after scraping, sanding, or mechanically cleaning if the plaster particles create a problem.

Our products should be applied on substructure surfaces that are built in line with 30.06.2007 dated General Construction Specifications No. 26568.

For airless spraying:

Pressure: 120-140 bar

Nozzle Angle: 50°

Nozzle Size (inch): 0.013"

Thinning: 5%

THINNING

Recommended to be applied in two coats after thinning by 10-15% with clean water in brush and roller applications.

DRYING TIME (at 20°C, 65% HR)

First drying: 1-2 hours

Paint application: 6 hours

CAUTION! Drying time is 6 hours when applied on water-based paint and 24 hours when applied on solvent-based paint (drying time can increase at higher relative humidity and lower temperature values).

CONSUMPTION

10-15 m² single coat per liter depending on the type, absorbency, and structure of the application surface. Perform a controlled sample run to estimate the precise consumption.

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frost and direct sunlight. Close the package right after application in an air-tight manner.

PACKAGING

20 kg, 3.5 kg

WARNING WORD



Caution

HAZARD PHRASE

H317 Causes allergic skin reactions.

PRECAUTIONARY PHRASES

P101 If medical advice is needed, have the product container or label at hand.

P102 Keep out of the reach of children.

P103 Read the label before use.

P261 Avoid breathing in dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment is required (see on this label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national, and international regulations.