



DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

Fawori Extra Ceiling

PRODUCT DESCRIPTION

Acrylic copolymer emulsion-based, decorative, matt white ceiling paint for interior surfaces.

SPECIFICATIONS

Fawori Ceiling Extra is a water-based paint with a high level of breathability. Matt and smooth finish. Adheres perfectly to surfaces. Features a high covering power. No blistering and flaking.

APPLICATION SURFACES

Fawori Extra Ceiling is preferred to be used on satin plaster, putty, plasterboard surfaces and old painted or primed interior ceiling surfaces with no dusting behavior.

APPLICATION

Ensure the application surface is smooth, secure and in a well condition to hold the primer and the top-coat paint. Clean all types of stain, dust, block grease, loose layers and make the required surface corrections. Comply with the defined setting periods on concrete, brute concrete and new plastered surfaces (28 days). Apply Fawori Gypsum Primer on absorbing and high dust generating surfaces like lime, plaster and whitewash before combing and polishing. Ensure the ambient and the surface temperature is between +5°C and +30°C during the application and until the product is fully dry, and protect the surfaces against frost. Apply using a brush, a roller or a sprayer.

Our products should be applied on substructure surfaces that are built in line with 30.06.2007 dated General Construction Specifications No. 26568.

For airless spraying:

Pressure	:	140 bar
Nozzle Angle	:	50°
Nozzle Size (inch)	:	0.019"
Thinning (Water)	:	10-15 % (Volume)

DILUTION

Recommended to be applied in two coats after thinning by 20% with clean water in brush and roller applications. Recommended to be applied in one coat provided that the sufficient film thickness is achieved after thinning by 10-15% with clean water in airless spraying.

DRYING TIME (at 20°C, 65% HR):

Touch dryness: 1 hour

Resting period between coats: 6 hour

Final drying: 24 hours (drying time can increase at higher relative humidity and lower temperature values)

CONSUMPTION

7-10 m² single coat per kilogram depending on the type, absorbency and structure of the application surface. Apply a sample area to estimate the net quantity needed.

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frosting and direct sunlight. Close the package right after application in an air-tight manner.

PACKAGING

20 kg, 17.5 kg, 10 kg, 3.5 kg

HAZARD DESCRIPTION

Xi Irritating.

RISK STATEMENTS

R 43: May cause sensitization by skin contact.

**SAFETY STATEMENTS:**

S 02: Keep out of the reach of children.

S 23: Do not breathe gas/fumes/vapor/spray.

S 24/25: Avoid contact with eyes and skin.

S 37/39: Wear suitable protective gloves. Wear eye/face protection.

S 46: If swallowed, seek medical advice immediately and show this container or label.

S 56: Dispose of this material and its container to hazardous or special waste collection point.



Complies with TS 5808/2012.



In compliance with the G communiqué.

TSE

Wet Rubbing Fastness: Class 5

Covering Power: Class 2 (7m²/L)

Granule Size: Class S1

Brightness: Class G3

This technical sheet is prepared based on laboratory data under normal conditions, consult to technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for the failures that may arise due to lack of knowledge. Our company reserves the right to change this information.

This product is manufactured by Betek A.Ş. having the certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.

Rev1 January 2014