

according to 1907/2006/EC, Article 31

Printing date 29.01.2015

Revision: 29.01.2015

#### 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: BETEK MATT SYNTHETIC PAINT
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation Alkyd resin based, top coat interior decorative paint.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Betek Boya ve Kimya Sanayi A. Ş. G.O.S.B. Tembelova Alanı 3200 Sokak No:3206 41400 Gebze/ Kocaeli/ Türkiye Tel: 00 90 262 678 30 00 Fax: 00 90 262 641 21 68
- · Further information obtainable from: R&D Department
- · Emergency telephone number: 0090 262 678 3000

#### 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

- *R65: Harmful: may cause lung damage if swallowed.*
- R10: Flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

• Classification system:

- The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Danger

according to 1907/2006/EC, Article 31

Printing date 29.01.2015

Revision: 29.01.2015

Trade name: BETEK MATT SYNTHETIC PAINT

(Contd. of page 1)

· Hazard-determ	ining components of labelling:
Solvent naphthe	a (petroleum), medium aliph.
· Hazard statem	ents
H226 Flammab	ole liquid and vapour.
H304 May be fo	atal if swallowed and enters airways.
Contains 2-but	anone oxime. May produce an allergic reaction.
· Precautionary	statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303+P361+P	353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
• Other hazards	
· Results of PBT	and vPvB assessment
· <b>PBT:</b> Not appli	

• **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	nts:	
CAS: 64742-88-7	Solvent naphtha (petroleum), medium aliph.	10-25%
EINECS: 265-191-7	🗙 Xn R65	
	🚯 Asp. Tox. 1, H304	
	2-butanone oxime	<i>≤</i> 2.5%
EINECS: 202-496-6	🗙 Xn R21-40; 🗙 Xi R41; 🗙 Xi R43	
	Xn R21-40; X R41; X R43 ⟨ Carc. 2, H351; ⟨ Eye Dam. 1, H318; ⟨ Acute Tox. 4, H312; Skin Sens. 1, H317	
· Additional informati	on: For the wording of the listed risk phrases refer to section 16.	

## 4 First aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

#### **5** Firefighting measures

- · Extinguishing media
- *Suitable extinguishing agents:* CO2, sand, extinguishing powder. Do not use water.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31

Printing date 29.01.2015

Revision: 29.01.2015

Trade name: BETEK MATT SYNTHETIC PAINT

(Contd. of page 2)

· For safety reasons unsuitable extinguishing agents: Water with full jet

• Advice for firefighters

· Protective equipment: No special measures required.

#### 6 Accidental release measures

• *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.* 

• *Environmental precautions:* Do not allow to enter sewers/ surface or ground water. • *Methods and material for containment and cleaning up:* 

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents **Pafarance to other sections** 

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

#### 7 Handling and storage

· Handling:

- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.*
- · Information about fire and explosion protection:

*Keep ignition sources away - Do not smoke. Protect against electrostatic charges.* 

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

## 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

GB

according to 1907/2006/EC, Article 31

Revision: 29.01.2015

#### Trade name: BETEK MATT SYNTHETIC PAINT

• Protection of hands:

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### • Eye protection:



Tightly sealed goggles

Information on basic physica	ul and chemical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Change in condition	
Melting point/Melting rang	ge: Undetermined.
Boiling point/Boiling rang	e: Undetermined.
Flash point:	43°C
Ignition temperature:	265°C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixture. are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	6.5 Vol %
Vapour pressure at 20°C:	6.6 hPa
Density at 20°C:	1.49 g/cm <sup>3</sup>
Solubility in / Miscibility with	h
water:	Fully miscible.
Other information	VOC (In can): 359 g/l
e e	VOC (After thinning): 453 g/l

(Contd. on page 5)

GF

according to 1907/2006/EC, Article 31

Printing date 29.01.2015

Revision: 29.01.2015

#### Trade name: BETEK MATT SYNTHETIC PAINT

(Contd. of page 4)

#### **10 Stability and reactivity**

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values relevant for classification:

#### 64742-88-7 Solvent naphtha (petroleum), medium aliph.

 Oral
 LD50
 >6500 mg/kg (rat)

 Dermal
 LD50
 >3000 mg/kg (rab)

 Inhalative
 LC50/4 h
 >14 mg/l (rat)

06 20 7 2 butanona ovima

96-29-7 2-	96-29-7 2-butanone oxime						
Oral	LD50	3700 mg/kg (rat)					
Dermal	LD50	200-2000 mg/kg (rat)					
Inhalative	LC50/4 h	20 mg/l (rat)					
64742-95-6 Solvent naphtha (petroleum), light arom.							
Oral	LD50	>6800 mg/kg (rat)					
Dermal	LD50	>3400 mg/kg (rab)					
Inhalative	LC50/4 h	>10.2 mg/l (rat)					

#### · Primary irritant effect:

- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

#### **12 Ecological information**

- · Toxicity
- Acquatic toxicity: No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. • Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 6)

GR

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 29.01.2015

Revision: 29.01.2015

#### Trade name: BETEK MATT SYNTHETIC PAINT

(Contd. of page 5)

## **13 Disposal considerations**

· Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- *Recommendation:* Disposal must be made according to official regulations.

Land transport ADR/RID	) (cross-border)	
3		
ADR/RID class:	3 (F1) Flammable liquids.	
Danger code (Kemler):	30	
UN-Number:	1263	
Packaging group:	III	
Hazard label:	3	
UN proper shipping nam	e: 1263 PAINT, special provision 640E	
Maritime transport IMD	G:	
<u> </u>		
3		
IMDG Class:	3	
UN Number:	1263	
Label	3	
Packaging group:	III	
EMS Number:	F-E,S-E	
Marine pollutant:	No	
Proper shipping name:	PAINT	
Air transport ICAO-TI an	nd IATA-DGR:	
V		
ICAO/IATA Class:	3	
UN/ID Number:	1263	
Label	3	
Packaging group:	III DAINT	
Proper shipping name:	PAINT	

(Contd. on page 7)

according to 1907/2006/EC, Article 31

Printing date 29.01.2015

Revision: 29.01.2015

#### Trade name: BETEK MATT SYNTHETIC PAINT

(Contd. of page 6)

GB

#### **15 Regulatory information**

· Safety, health and environmental regulations/legislation specific for the substance or mixture

• National regulations: Class Share in %

I 0.7 NK 22.2

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H304 May be fatal if swallowed and enters airways.

- H312 Harmful in contact with skin.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H351 Suspected of causing cancer.
- R21 Harmful in contact with skin.
- R40 Limited evidence of a carcinogenic effect.
- *R41 Risk of serious damage to eyes.*
- *R43* May cause sensitisation by skin contact.
- *R65* Harmful: may cause lung damage if swallowed.
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organization
- ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent