

Printing date 26.01.2015 Revision: 26.01.2015

## 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: BETEK IMPREGNATION CARE
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation

Modified alkyd resin based, contains impregnation material which protects wood against microorganisms.

- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Betek Boya ve Kimya Sanayi A.S.

G.O.S.B. Tembelova Alani 3200 Sokak No:3206

41400 Gebze/ Kocaeli/ Türkiye Tel: 00 90 262 678 30 00 Fax: 00 90 262 641 21 68

- · Further information obtainable from: R&D Department
- · Emergency telephone number: 00 90 262 678 30 00

## 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



T; Toxic

*R45-46: May cause cancer. May cause heritable genetic damage.* 



Xn; Harmful

*R65:* Harmful: may cause lung damage if swallowed.



Xi; Sensitising

*R43: May cause sensitisation by skin contact.* 

R10-52/53: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

(Contd. on page 2)

Printing date 26.01.2015 Revision: 26.01.2015

Trade name: BETEK IMPREGNATION CARE

(Contd. of page 1)

#### · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

· Signal word Danger

#### · Hazard-determining components of labelling:

Solvent naphtha (petroleum), medium aliph. Naphtha (petroleum), hydrotreated heavy tolylfluanid (ISO)

#### · Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

## · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 26.01.2015 Revision: 26.01.2015

Trade name: BETEK IMPREGNATION CARE

	(Conto	d. of page 2)
· Dangerous compone	ents:	
CAS: 64742-88-7 EINECS: 265-191-7	Solvent naphtha (petroleum), medium aliph.  Xn R65  ♦ Asp. Tox. 1, H304	50-100%
CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy  ☐ T R45;  Xn R65  ☐ Carc. 1B, H350; Asp. Tox. 1, H304	2.5-10%
CAS: 731-27-1 EINECS: 211-986-9	tolylfluanid (ISO)  ☐ T+ R26; ☐ T R48/23; ☐ Xi R36/37/38; ☐ Xi R43; ☐ N R50  ☐ Acute Tox. 3, H331; ⑤ STOT RE 2, H373; ⑥ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≤ 2.5%
CAS: 96-29-7 EINECS: 202-496-6	2-butanone oxime  Xn R21-40; X Xi R41; X Xi R43  ◆ Carc. 2, H351; ◆ Eye Dam. 1, H318; ◆ Acute Tox. 4, H312; Skin Sens. 1, H317	≤ 2.5%

<sup>·</sup> Additional information: For the wording of the listed risk phrases refer to section 16.

## 4 First aid measures

- Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

#### 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

(Contd. on page 4)

Printing date 26.01.2015 Revision: 26.01.2015

Trade name: BETEK IMPREGNATION CARE

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 26.01.2015 Revision: 26.01.2015

Trade name: BETEK IMPREGNATION CARE

(Contd. of page 4)

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic

· Change in condition

**Melting point/Melting range:** Undetermined. **Boiling point/Boiling range:** Undetermined.

· Flash point: <39°C</li>· Ignition temperature: 265°C

· Self-igniting: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures

are possible.

· Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 6.5 Vol %

· Vapour pressure at 20°C: 6.6 hPa

• **Density at 20°C:** 0.8 g/cm<sup>3</sup>

· Solubility in / Miscibility with

water: Fully miscible.

Solvent content:

**VOC (EC)** 736 g/l

## 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Hazardous decomposition products: No dangerous decomposition products known.

- G

Printing date 26.01.2015 Revision: 26.01.2015

Trade name: BETEK IMPREGNATION CARE

(Contd. of page 5)

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

	· LD/LC50 values relevant for classification:				
	64742-88-	64742-88-7 Solvent naphtha (petroleum), medium aliph.			
Ī	Oral	LD50	>6500 mg/kg (rat)		
	Dermal	LD50	>3000 mg/kg (rab)		
	Inhalative	LC50/4 h	>14 mg/l (rat)		
Ī	64742-48-9 Naphtha (petroleum), hydrotreated heavy				
Ī	Oral	LD50	>5000 mg/kg (rat)		
	Dermal	LD50	>3000 mg/kg (rab)		

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

· Sensitisation May cause sensitisation by skin contact.

## 12 Ecological information

- · Toxicity
- · Acquatic toxicity: No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### 13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

GB

Printing date 26.01.2015 Revision: 26.01.2015

Trade name: BETEK IMPREGNATION CARE

(Contd. of page 6)

## 14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 (F1) Flammable liquids.

Danger code (Kemler): 30
UN-Number: 1263
Packaging group: III
Hazard label: 3

· UN proper shipping name: 1263 PAINT, special provision 640E

· Maritime transport IMDG:



· IMDG Class: 3
· UN Number: 1263
· Label 3
· Packaging group: III
· EMS Number: F-E,S-E
· Marine pollutant: No
· Proper shipping name: PAINT

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3
· UN/ID Number: 1263
· Label 3
· Packaging group: III
· Proper shipping name: PAINT

- · UN "Model Regulation": UN1263; PAINT; 3; III
- · Special precautions for user Warning: Flammable liquids.

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:

Class	Share in %
I	1.6
NK	85.8

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 26.01.2015 Revision: 26.01.2015

Trade name: BETEK IMPREGNATION CARE

(Contd. of page 7)

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevan	t phrases
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

- H410 Very toxic to aquatic life with long lasting effects.
- R21 Harmful in contact with skin. R26 Very toxic by inhalation.
- R36/37/38 Irritating to eyes, respiratory system and skin.
  R40 Limited evidence of a carcinogenic effect.
  R41 Risk of serious damage to eyes.
- R43 May cause sensitisation by skin contact.
- R45 May cause cancer.
- R48/23 Toxic: danger of serious damage to health by prolonged exposure through inhalation.
- *R50 Very toxic to aquatic organisms.*
- *R65 Harmful: may cause lung damage if swallowed.*

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent