

According to the Regulation REACH EC 2020/878

## Road marking paint - White and Yellow - Road marking paint

Date Prepared : Aug. 15, 2023  
Revision : 0

Revision Date : 09.08.2025  
SDS No : GBF – 2151

### IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

#### 1.1- Product Identifier

Product Name SIGNALINE

#### 1.2- Relevant identified uses of the substance advised against

Identified uses This paint is used in all kinds of city and intercity road, parking lot and other areas are drawn  
Usage advised against No data available

#### 1.3- Details of the supplier of the substance or mixture

Importer: Ada Color Ltd.  
st. "Brezovsko Shose" 176,  
4003 Plovdiv, Bulgaria  
mobile: +359896663052  
tel: +35932940456  
fax: +35932940457  
web: adacolor-bg.com

#### 1.4- Emergency telephone number

Additional information: Bulgaria:

Toxicology Clinic at the National Medical University of Sofia "N. I. Pirogov"

Emergency telephone number:

+359 02 9154 409 (during standard working hours excluding Saturdays and Sundays)  
+359 02 9154 346 (24/7 service)

### HAZARDS IDENTIFICATION

#### 2.1- Classification of the substance:

**According to the Regulation of EC 1272/2008 (CLP):**

Flammable Liquid, Category 2, H225

Skin Irritation, Category 2, H315

Specific Target Organ Toxicity, Single Exposure, Category 3, H336

Reproductive System Toxicity, Category 2, H361

Specific Target Organ Toxicity, Repeated Exposure, Category 2, H373 (Central Nervous System)

#### 2.2- Label elements:

**According to the Regulation of EC 1272/2008 (CLP):**

**Hazard Pictograms:**



**Signal word** Danger

**Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

According to the Regulation REACH EC 2020/878

## Road marking paint - White and Yellow - Road marking paint

- H336 May cause drowsiness or dizziness  
 H361 Suspected of damaging fertility or the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure

### Precautionary statements

#### Prevention

Date Prepared : Aug. 15, 2023 Revision Date : 09.08.2025  
 Revision : 0 SDS No : GBF – 2151

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 P233 Keep container tightly closed.  
 P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P264 Wash hands thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### Response

- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. – Rinse skin with water/shower.  
 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P321 Specific treatment (see ... on this label).  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P362 Take off contaminated clothing and wash before reuse.  
 P370+P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction  
 P302+P352 IF ON SKIN: Wash with plenty of soap and water  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

#### Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

#### Disposal

- P501 Dispose of contents/containers to the local regulations.

### 2.3- Other Hazards:

Not applicable

## COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2- Substance

Chemical name	EC No.	CAS No.	%	Classification
---------------	--------	---------	---	----------------

According to the Regulation REACH EC 2020/878

## Road marking paint - White and Yellow - Road marking paint

Toluene	203-625-9	108-88-3	$10 \leq X < 25$	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Repr. 2, H361
Ethyl Acetate	205-500-4	141-78-6	$2,5 \leq X < 10$	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Calcium carbonate	471-34-1		$50 < X < 60$	This substance does not meet the criteria for classification in accordance with Regulation No 2020/878

Full text of H-statements: see section 16.

### 4.1- Description of first aid measures

#### General

Call a POISON CENTER or doctor/physician if you feel unwell.

#### Skin contact

Contact may cause moderate skin irritation during use. Avoid prolonged exposure to skin products. Wash the irritant area with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

#### Eye contact

Contact with product may cause severe eye irritation. In case of contact with liquid, rinse affected eye with clean water for at least 15 minutes. If irritation occurs: Get medical advice/attention.

#### Inhalation

In case of inhalation, no significant effect is observed. As a precaution, remove the victim to fresh air and hold him in a comfortable position for easy breathing. If irritation persists, seek medical attention.

#### Ingestion

Under normal circumstances there is no chance of coming in. No significant irritation.

## FIRE FIGHTING MEASURES

### 5.1- General information

The product is classified as flammable. Flash point  $\leq 21$  °C

### 5.2- Suitable Extinguishing Media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Never use water to extinguish.

### 5.3- Special hazards arising from the substance or mixture

No data available.

### 5.1- Special hazards arising from the substance or mixture

Wear full protective clothing including self-contained breathing apparatus for firefighting if necessary.

### 5.2- Special methods

Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilation/flammable/material.

## Road marking paint - White and Yellow - Road marking paint

### ACCIDENTAL RELEASE MEASURES

#### 6.1- Personal precautions, protective equipment, and emergency procedures

Avoid contact with eyes and skin of the product. Use personal protective equipment. Make sure of good ventilation. In case of insufficient ventilation wear suitable respiratory equipment.

#### 6.2- Environmental precautions

Collect contaminated/extinguishing water. Place spilled material in a container to dispose of non-combustible absorbent materials such as sand, earth, vermiculite, and diatomaceous earth in accordance with local regulations. (see section 13). Do not allow it to interfere with water, soil and sewage.

#### 6.3- Methods and materials for containment and cleaning up

This is a dangerous waste. Collect and packaging back for recycling or disposal.

#### 6.4- Reference to other sections

Information on safe handling is given in section 7. Information on personal protective equipment is given in section 8. Disposal information from chapter 13

### HANDLING AND STORAGE

#### 7.1- Precautions for safe use

Ensure that the work area is well ventilated. Avoid long-term contact with your eyes and skin. Wash thoroughly with detergent after handling.

#### 7.2- Condition for safe storage, including any incompatibilities

Keep away from strong solvents and extreme heat. Store in a dry and well-ventilated enclosed area. Store in its original packaging. Take precautions against static discharges. The product can be electrostatically charged; Wear antistatic shoes and clothes. Protect from all kinds of fire and heat source, sunlight. Do not smoke.

#### 7.3- Specific end use(s)

Road marking paint.

### EXPOSURE CONTROLS, PERSONAL PROTECTION

#### 8.1- Exposure Limit Values

##### Control parameters

- OSHA:

Toluene (108-88-3)

TWA 200 ppm

STEL 100 ppm

Ethyl Acetate (141-78-6)

TWA 5 ppm

STEL 25 ppm

#### 8.2- Exposure controls



General Protection and Hygiene Measures

Keep the container tightly closed. Wash your hands at the end of the work and break. Do not eat or drink any food while using this product.

Respiratory protection

No respiratory protection is required. Use a mask according to EN 143 if necessary.

Eye/Face protection

Use safety goggles in accordance with EN 166 with side-shielded, which fit perfectly into areas where there is a high risk of splashing. It is advisable to have a shower in the work area.

Hand protection

Use butyl rubber or nitrile gloves in accordance with EN 374. Protective cream can be used before starting work. Do not clean with cream after coming into contact with paint.

Body protection

If necessary, use work clothes in accordance with EN 465 or EN 467 and work shoes in accordance with EN 347 standards.

## Road marking paint - White and Yellow - Road marking paint

### 8.3- Environmental exposure controls

The provisions of existing legislation for the protection of the environment must be fully implemented.

## 9- PHYSICAL AND CHEMICAL PROPERTIES

### 9.1- Information on basic physical and chemical properties:

Physical State	Liquid
pH	Not determined.
Boiling point, °C	133.20 °C.
Flash point, °C	33.42 °C.
Vapor pressure (hPa) (20°C)	below 110 kPa (1.10)
Density @ 20°C, gr/m <sup>3</sup>	> 1
Solubility in water @ 20°C	insoluble.

### 9.2- Other Information:

Melting Point, ° C	Not determined.
Decomposition Point, ° C	Not determined.
Self-ignition Temperature, ° C	Not determined.

## 10- STABILITY AND REACTIVITY

### 10.1- Reactivity

The substance is stable under normal storage and handling conditions.

### 10.2- Possibility of hazardous reactions

Under normal circumstances, reactions that may occur are not dangerous.

### 10.3- Conditions to avoid

Do not expose to incompatible materials.

### 10.4- Substances to avoid

Avoid strong acids and alkaline solutions that will damage the surface appearance of the material.

### 10.5- Hazardous decomposition products

The thermal decomposition product may contain various liberated carbon oxides.

## 11- TOXICOLOGICAL INFORMATION

### 11.1- Information on toxicological effects

Acute toxicity	No data available.
Components:	
Toluene (108-88-3)	
Oral	LD50: > 5000 mg/kg
Inhalation	LC50: 5320 ppm (8 h)
Dermal	LD50: > 5000 mg/kg
Ethyl Acetate (141-78-6)	
Oral	LD50: 5620 mg/kg
Inhalation	LC50: > 18 mg/l (4 h)
Dermal	LD50: > 20000 mg/kg

### 11.2- Corrosion and irritation

Serious eye damage/irritation	No data available.
-------------------------------	--------------------

## Road marking paint - White and Yellow - Road marking paint

Skin corrosion/irritation	Causes skin irritation
Skin sensitization	Causes skin irritation.
Respiratory sensitization	No data available.
Respiratory tract irritation	May cause damage to organs through prolonged or repeated exposure.

### 11.3- Chronic effects

Carcinogenicity	Not listed in ACGIH, IARC or NTP.
-----------------	-----------------------------------

### 11.4- Other Toxicity Effects

Mutagenicity	No data available.
Reproduction toxicity	Suspected of damaging fertility or the unborn child.
Epidemiology	No data available
Teratogenicity	No data available
Specific Target Organ Toxicity - Single Exposure	May cause drowsiness or dizziness
Specific Target Organ Toxicity - Repeated Exposure	May cause damage to organs through prolonged or repeated exposure

## ECOLOGICAL INFORMATION

### 12.1- Toxicity

Product-related data is not available.

Components:

Toluene (108-88-3)	
Acute fish toxicity	LC50: 57,68 mg/l (96 h)
Acute daphnia magna toxicity	EC50: 11.5 mg/l (48 h)
Acute algae toxicity	NOEC:> 400 mg/l (7 d)
Ethyl Acetate (141-78-6)	
Acute fish toxicity	LC50: 900 mg/l (48 h)
Acute daphnia magna toxicity	EC50: 260 mg/l (48 h)
Acute algae toxicity	NOEC:> 100 mg/l (72 h)

### 12.2- Persistence and degradability

No data available.

### 12.3- Bioaccumulative potential

No data available.

### 12.4- Mobility in soil

No data available.

### 12.5- Results of PBT and vPvB assessment

No data available.

### 12.6- Other adverse effects

No data available.

## DISPOSAL CONSIDERATIONS

### 13.1- Waste treatment methods

Material may be hazardous and special handling may be required for disposal. Not given to sewer. Disposal in storage must comply with federal, state and local regulations.

## Road marking paint - White and Yellow - Road marking paint

### TRANSPORT INFORMATION

#### Land transport (ADR / RID)

14.1- UN number	UN1263
14.2- Proper UN transport name	Paint
14.3- Transport hazard class(es)	3
14.4- Packing group	III
14.5- Environmental hazards	Not harmful to the environment.
14.6- Bulk transport according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
Limited quantity (ADR/RID)	5 L
Tank code (ADR/RID)	LGBF
Vehicle for tanker	FL
Tunnel ode	2 (D/E)
Hazard identification no.	33
Orange plates	

33
1263



#### Sea transport (IMDG Code)

14.1- UN number	UN1263
14.2- Proper UN transport name	Paint
14.3- Transport hazard class (es)	3
14.4- Packing group	III
14.5- Environmental hazards	Not harmful to the environment.
14.6- Bulk transport according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
Limited quantity (IMDG)	LQ
EmS No (Fire)	F-E
N*FS (Spill)	S-E



#### Air Transport (ICAO-IATA/DGR)

14.1- UN number	UN1263
14.2- Proper UN transport name	Paint
14.3- Transport hazard class (es)	3
14.4- Packing group	III
14.5- Environmental hazards	Not harmful to the environment.
14.6- Bulk transport according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.



## Road marking paint - White and Yellow - Road marking paint

### REGULATORY INFORMATION

#### 15.1- Safety, health and environmental regulations specific for the substance or mixture

- Regulation (EC) No 1907/2006, (REACH),
- Commission Regulation (EU) No 453/2010 amending Regulation (EC) No 1907/2006,
- Regulation (EC) No 1272/2008 (CLP),
- Commission Directive 2006/15/EC,
- Commission Directive 2000/39/EC
- Council Directive 91/689/EEC,
- ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

### OTHER INFORMATION

#### 16.1- The relevant H phrases (number and full text):

- H225** Highly flammable liquid and vapour.  
**H304** May be fatal if swallowed and enters airways.  
**H315** Causes skin irritation.  
**H319** Causes serious eye irritation.  
**H336** May cause drowsiness or dizziness.  
**H361** Suspected of damaging fertility or the unborn child.  
**H373** May cause damage to organs through prolonged or repeated exposure

#### 16.2- Abbreviations and acronyms

- ADR : European Agreement Concerning the Int. Carriage of Dangerous Goods by Road  
CAS No : Chemical Abstract Service Index Number  
EC No : European Commission Number  
EC50 : Concentration which produces a certain effect under the conditions determined in 50% of the organisms subjected to the test  
IATA : International Air Transport Association  
ICAO : International Civil Aviation Organization  
IMDG : International Maritime Code for Dangerous Goods  
LC50 : Lethal Concentration 50% (Substance concentration should be in the air to kill 50% of the test animals)  
LD50 : Lethal Dose 50% (The amount of substance required to be dosed at a time to kill 50% of test animals)  
REACH : Regulation on the Registration, Evaluation, Authorisation and Restriction of Chemicals in the European Union  
STEL : Short Term Exposure Limit  
TWA : Time Weighted Average

#### 16.3- Further Information:

This safety data sheet has been prepared in accordance with the information received from the product owner. The information in this document is based on the best available information. This information applies only to the specified substance/preparation.

The information given in this document does not constitute a guarantee/warranty for the product specifications and does not constitute a legally binding contract/contingent legal relationship feature. This document completes the technical documentation but can not be replaced. The information provided is based on our current knowledge of the product at the time of publication. Based on good goodness.

We do not accept responsibility for the product and information provided for similar materials not manufactured or supplied by SIGNATEKMA Boya ve Sinyalizasyon San. ve Tic. A.Ş.