

according to 1907/2006/EC, Article 31

Printing date 26.01.2015

Revision: 26.01.2015

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- Trade name: BETEK BOXAN 451
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation Hygienic liquid
- Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Betek Boya ve Kimya Sanayi A.S. G.O.S.B. Tembelova Alani 3200 Sokak No:3206 41400 Gebze/ Kocaeli/ Türkive Tel: 00 90 262 678 30 00 Fax: 00 90 262 641 21 68

· Further information obtainable from: R&D Department

· Emergency telephone number: 0090 262 678 3000

2 Hazards identification

· Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Skin Corr. 1A H314 Causes severe skin burns and eye damage.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.01.2015

Revision: 26.01.2015

Trade name: BETEK BOXAN 451

	(Contd. of page 1)
· Hazard-deter	mining components of labelling:
	ethylsiliconate
· Hazard states	ments
H225 Highly	flammable liquid and vapour.
	severe skin burns and eye damage.
· Precautionar	y statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P303+P361+	P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
• Other hazard	ls –
· Results of PE	3T and vPvB assessment
• PBT: Not app	plicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 31795-24-1	Potassium methylsiliconate	2.5-10%	
EINECS: 250-807-	9 🚰 C R35 🔄 Skin Corr. 1A, H314		
CAS: 35435-21-3	Triethoxy (2,4,4-trimethylpentyl)silane	< 2.5%	
EINECS: 252-558-	1 R10-52/53	_	
	🚸 Flam. Liq. 3, H226; Aquatic Chronic 3, H412		
CAS: 1310-58-3	potassium hydroxide	<i>≤</i> 2.5%	
EINECS: 215-181-	3 🔁 C R35; 🗙 Xn R22		
	📀 Skin Corr. 1A, H314; 🚸 Acute Tox. 4, H302		
· Additional informa	tion: For the wording of the listed risk phrases refer to section 16.		

4 First aid measures

· Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

• *After inhalation:* In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• *After swallowing:* Drink plenty of water and provide fresh air. Call for a doctor immediately.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31

Printing date 26.01.2015

Revision: 26.01.2015

Trade name: BETEK BOXAN 451

 $(Contd. \ of page \ 2)$

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

- Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

1310-58-3 potassium hydroxide

- WEL Short-term value: 2 mg/m³
- Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

GB –

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.01.2015

Revision: 26.01.2015

Trade name: BETEK BOXAN 451

(Contd. of page 3)

· Exposure controls

- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical of General Information	and chemical properties	
Appearance:		
Form:	Fluid	
Colour:	According to product specification	
Odour:	Characteristic	
pH-value at 20°C:	11-13	
Change in condition Melting point/Melting range: Boiling point/Boiling range:		
Flash point:	Not applicable.	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.01.2015

Revision: 26.01.2015

Trade name:	BETEK BOXAN 451
ruuc nume.	

		(Contd. of page
· Vapour pressure at 20°C:	23 hPa	
Density at 20°C:	1.04-1.06 g/cm ³	
· Solubility in / Miscibility wit water:	i Fully miscible.	
Solvent content: VOC (EC)	5 g/l	
Solids content:	9-11 %	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

12 Ecological information

- · Toxicity
- · Acquatic toxicity: No further relevant information available.
- Additional ecological information:
- General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.

(Contd. on page 6)

GB

according to 1907/2006/EC, Article 31

Printing date 26.01.2015

Revision: 26.01.2015

Trade name: BETEK BOXAN 451

(Contd. of page 5)

• **vPvB:** Not applicable.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- *Recommendation:* Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class:	3 (F1) Flammable liquids.	
· Danger code (Kemler):	30	
· UN-Number:	1263	
· Packaging group:	11	
· Hazard label:	3	
· UN proper shipping name:	: 1263 PAINT RELATED MATERIAL, special provision 640D	
• Tunnel restriction code	D/E	
• Maritime transport IMDG	:	
3		
· IMDG Class:	3	
· UN Number:	1263	
· Label	3	
· Packaging group:	11	
· EMS Number:	F-A,S-B	
· Marine pollutant:	No	
· Segregation groups	Flammable liq.	
· Proper shipping name:	PAINT RELATED MATERIAL	
· Air transport ICAO-TI and	l IATA-DGR:	
· ICAO/IATA Class:	3	
· UN/ID Number:	1263	
· Label	3	
· Packaging group:	II	
• Proper shipping name:	PAINT RELATED MATERIAL	
		(Contd. on page 2

according to 1907/2006/EC, Article 31

Printing date 26.01.2015

Revision: 26.01.2015

Trade name: BETEK BOXAN 451

(Contd. of page 6)

· UN "Model Regulation": UN1263, PAINT RELATED MATERIAL, 3, II

· Special precautions for user Warning: Flammable liquids.

15 Regulatory information

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H412 Harmful to aquatic life with long lasting effects.

R10 Flammable.

R22

Harmful if swallowed. R35 Causes severe burns.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)

GB