



DECORATIVE SYNTHETIC PRODUCT GROUP

Betek Kapatan

DESCRIPTION

Thermoplastic resin-based, matte, interior paint that prevents the stains to be seen from the surface by perfectly covering stains on painted or unpainted surfaces like smudge, nicotine, grease, moisture, graffiti (paint, ink, marker/stencil, lipstick etc.) and traces of fire.

SPECIFICATIONS

Can be applied on all types of surfaces without requiring much preparation. Resistant against moisture stains, mold and chipping. Can be wiped with water and detergent. Preserves its whiteness, does not turn yellow. Does not contain lead, not harmful to the health. Doesn't have an irritating smell since it has no aroma. The application surface can be used a short time after its application.

APPLICATION SURFACES

Can be applied on all types of painted or unpainted surfaces (walls/ceilings) at indoors.

APPLICATION

Ensure the application surface is smooth, secure and in a well condition to hold the primer and the top-coat paint. Clean all types of stain, rust, dust, block grease, loose layers and make the required surface corrections. Sand the surfaces using fine grained emery paper before starting to apply primer on old painted water-solvent based surfaces.

Apply as two coats using a brush or a roller without thinning. May be required to apply three coats on very dirty surfaces. Sand the surface and apply Betek Primer if water-based paint will be applied over Betek Kapatan. Apply the paint only after these steps. Apply solvent-based paint directly on Betek Kapatan.

Ensure the ambient and the surface temperature is between +5°C and +30°C during the application and until the product is fully dry, and protect the surfaces against frost. Clean the tools used with Betek Synthetic Thinner immediately after application.

You can access the MSDS and TDS forms including the information regarding detailed application, healthy-safety-handling risks and precautions on www.betekexport.com.

THINNING

Ready to use.

DRYING TIME (at 20°C, 65% HR):

Touch drying is completed in 1-2 hours. Wait 8 hours between each coat (drying time can increase at higher relative humidity and lower temperature values).

CONSUMPTION

5-7 m² single coat per liter depending on the type, absorbency and structure of the application surface. Perform a controlled sample run to estimate the precise consumption.

FLASH POINT

36°C

STORAGE

May be stored for at least 3 years in its unopened packaging in a cool and dry environment protected against frosting and direct sunlight. To preserve the remaining product in the best way in its package, close its cover tightly and shake for 1-2 times.

PACKAGING

2.5 Liters

HAZARD DESCRIPTION

Xn Hazardous to health.

Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/

Ingredients identifying the hazard for labeling:

ALKANES, C9-12-ISO-

This technical sheet is prepared based on laboratory data under normal conditions, consult to technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for the failures that may arise due to lack of knowledge. Our company reserves the right to change this information.