

**TECHNICAL DATA SHEET**

## Rust Converter spray



Rust Converter – rust converter in spray is a primer designed for rusty surfaces. Thanks to its reactivity with rust and iron, it transforms rust into stable base coat which can be covered with most coat types available on the market.

**FOR PROFESSIONAL USE!**

### USE

---

- ◆ repair and maintenance of vehicles,
- ◆ renovation of devices of various types,
- ◆ agricultural machinery,
- ◆ containers,
- ◆ steel constructions.

Typical use consists in covering damaged or rusted metal parts.

**Attention!** Application temperature 8°C - 25°C

### PRODUCT CHARACTERISTICS

---

- ◆ Excellent conversion.
- ◆ Excellent adhesion.
- ◆ Cured surface is easy to sand.

### COLOUR

---

Brown.

### INSTRUCTION FOR USE

---

Remove mechanically as much rust as possible by polishing or brushing the surface. Shake carefully the container before use. Apply on a surface from the distance of 20-30 cm. Apply 2 or 3 thin layers “wet on wet” with no dripping. Wait for 5 -10 min before the application of succeeding layers. Leave the layer for conversion and drying (about 10 - 12 hours). Sand dried coat to increase adhesion of the next coat.

## TECHNICAL DATA SHEET

### STORAGE CONDITIONS

---

Store in a dark and dry place away from fire and heat sources. The shelf life in original package at 20°C is 24 months.

### HEALTH AND SAFETY RECOMMENDATIONS

---

According to Material Safety Data Sheet of Dangerous Substance for particular product.

### PACKAGING

---

Art. No	Capacity, ml:	Package, pcs.:	Package weight, kg:
80684	200	12	2,70

This information is based on careful laboratory research and many years of experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.