



DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

BETEK GEL PRIMER

PRODUCT DESCRIPTION

A copolymer emulsion-based, ready-to-use, transparent, plaster primer developed to provide solution to issues faced in paint applications with conventional primers, preventing high absorbency of the plaster surfaces.

SPECIFICATIONS

- Does not drip.
- Spreads equally.
- Fast- and easy-application.
- May be applied on both the ceilings and the walls.

Forms a bridge between the paint and the surface. Enables the top-coat paint layer to integrate with the application surface by penetrating deep into the application surface with a high penetration ability. Prevents the paint to dry early especially during hot weather conditions and decreases paint consumption by preventing surface absorption.

APPLICATION SURFACES

Used for priming very absorbent and/or high dust generating surfaces like plastered, poor quality absorbent plastic painted surfaces and aerated concrete before all types of interior plastic and silicon paint applications.

APPLICATION

Ensure that the application surface is smooth, secure and able to bear the primer and top-coat paint. Clean all types of stain, dust, block grease, loose layers and make the required surface corrections. Comply with the defined setting periods on concrete, brute concrete and new plastered surfaces (28 days).

Sand plaster and similar surfaces, remove dust with a damp-dry cloth and apply Betek Gel Primer. Start the paint application 4-6 hours after applying Betek Gel Primer. Ensure that the ambient and surface temperatures are between +5°C and +30°C during application and until the products are fully dried, and protect the surfaces against frost. Apply Betek Gel Primer using a brush or a roller without combing/polishing (by rolling the roller in one direction once) in a way that will not create a glassy surface. Dull the surface with sandpaper if a glassy surface is created. Avoid airless spraying method.

THINNING

Ready-to-use, never thin. The product may lose its anti-drip and anti-splash quality if thinned.

DRYING TIME (@ 20°C, 65% RH)

Touch dryness: 20 minutes

Paint application: 4-6 hours (drying time can increase at higher relative humidity and lower temperature values).

CONSUMPTION

15-20 m² single coat per liter depending on the type, absorbency and structure of the application surface. Perform a controlled sample run to estimate the precise consumption.

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGING

15 L, 7.5 L, 2.5 L

WARNING WORD

Caution

HAZARD PHRASE

H 317: May cause an allergic skin reaction.

PRECAUTIONARY PHRASES

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of the reach of children.

P103: Read label before use.



P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P321: Specific treatment (see on this label).

P363: Wash contaminated clothing before reuse.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P501: Dispose of contents/container in accordance with local, regional, national and international regulation.

This technical sheet is prepared based on laboratory data at normal conditions, consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for the failures that may arise due to a lack of knowledge. Our company reserves the right to change this information. Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks and precautions associated with the products.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

Rev0 January 19