

FEATURES

- Provides a modern look on the applied environments with its sparkling surface
- Due its high vapor permeability, it allows surface to discharge the steam and breathe.
- During application it covers up the faults on the surface with the thick layer of film that forms.
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odour in the application environments with its perfumed feature.

APPLICATION AREA

It is used in all kinds of interior/exterior surfaces, on mineral surfaces like rough plaster, exposed concrete, surfaces with old paint on it or cement sheet, with its suitable primer.

SURFACE PREPARATION

After cleaning all kinds of dirt, oil, blistered paint and dust from the application surfaces, surface defects should be corrected with **SAN DECO Acrylic Putty Interior** and surfaces should be primed with **SAN DECO Decoprimer**.

APPLICATION INSTRUCTIONS

- After primer application, apply **DECOCAM** with steel trowel as single coat. **DECOCAM** can be used without dilution, but water can also be added to achieve the desired consistency for easier application
- Product should be spread in even thickness to the entire surface with steel trowel. Trowel should be cleaned sometimes if it is needed.
- The environment of application must be kept between +5 °C to +35 °C within 24 hours during and after the application.

TECHNICAL DATA

DENSITY (g/cm³)	1,80±0,02
VISCOSITY (Krebs Unit)	Viscous
FLASH POINT	Water based
PH	8-9
SOLID CONTENT % wt	87±2
VOC (g/lt) (EU Directive 2004/42/EC) Calculated theoretically.	7
DILUTION	Look at the application instructions
COLOR	Decocam Color Chart
THEORETICAL CONSUMPTION * (g/m²) (For one coat)	4500 - 5000
COVERING CAPACITY (m²/Kg)	0,20 - 0,25
DRYING TIME (at 23°C)	Touch dry time 24 hours, Complete dry time 48-72 hours
SHELF LIFE**	1 Year
PACKAGING	20 Kg

* Theoretical Consumption Values are calculated for a single coat application with the condition of the surface smoothness, its porosity and application methods.

** Shelf life is valid when the product is stored in its sealed package at cool and dry place, protected from direct sunlight and at storage temperature + 5°C and + 35°C conditions.

WARNINGS/ PRECAUTIONS

- **P 102** Keep out of reach of children.
- **P 301+ P 310 IF SWALLOWED:** Immediately call a **POISON CENTRE** or doctor/physician.
- Don't use the containers for food preservation.