

DECOPIA is an acrylic emulsion base decorative interior final coat finish paint. It consists of prismatic three dimensional pearl and this provides color effects of different looks according to different angle of lights and also gives glittering effect through.

FEATURES

- Thanks to special prismatic mother of pearls that it includes, 3 different colors can be seen depending on lightening and point of view
- It can be wiped with water.
- Due its high vapor permeability, it allows surface to discharge the steam and breathe
- As it is water-based, it is harmless to human health and environment
- It provides a pleasant odour in the application environments with its perfumed feature.

APPLICATION AREA

It can be used for decorative and protective purposes on all kinds of surfaces such as wooden, wall, concrete panels, and satin plaster regardless of old painted or newly painted surfaces.

SURFACE PREPARATION

- After removing all kinds of dirt, grease, bloated paint and dust from the application surface, the surface defects should be corrected with **SAN DECO Acrylic Putty Interior** and undercoated with **SAN DECO Uniprimer**.
- It is advised to use **SAN DECO Decoplas** matt interior paint with desired color on primer applied before.
- **Decoplas** should be diluted for 10-15 % in volume with clean water; then applied in two coats with roller or brush without allowing traces. 4 hours should be allowed between each coat.

APPLICATION INSTRUCTIONS

- After undercoat is dried, **DECOPIA** is applied on surface as one coat with brush or roller without diluting. Preferred method of application is with special brush application
- The environment of application must be kept between +5 °C to +35 °C within 24 hours during and after the application.

TECHNICAL DATA

DENSITY (g/cm³)	1,02±0,02
VISCOSITY (Krebs Unit)	80-90
FLASH POINT	Water based
PH	8-9
SOLID CONTENT % wt	24±2
VOC (g/lit) (EU Directive 2004/42/EC) Calculated theoretically.	48
DILUTION	No
COLOR	Decopia Color Chart
THEORETICAL CONSUMPTION * (ml/m²) (For one coat)	50 - 60
COVERING CAPACITY (m²/L)	16,5 - 20,0
DRYING TIME (at 23°C)	Touch dry time 2-3 hours, Complete dry time 24 hours
SHELF LIFE**	1 Year
PACKAGING	1 L

* Theoretical Consumption Values are calculated for a single coat application with the condition of the surface smoothness, its porosity and application methods.

** Shelf life is valid when the product is stored in its sealed package at cool and dry place, protected from direct sunlight and at storage temperature + 5°C and + 35°C conditions.

WARNINGS/ PRECAUTIONS

- **P 102** Keep out of reach of children.
- **P 301+ P 310 IF SWALLOWED:** Immediately call a **POISON CENTRE** or doctor/physician.
- Don't use the containers for food preservation.