



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018
Printed on 28/02/2020
Page n. 1/18
Replaced revision:9 (Dated: 31/05/2018)

VP850.77.0000
POLYURETHANE VARNISH SEALER

Safety Data Sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: VP850.77.0000
Product name: POLYURETHANE VARNISH SEALER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Polyurethane based two component clear base coat.

1.3. Details of the supplier of the safety data sheet

Name: KAYALAR KIMYA SAN.VE TIC.A.S.
Full address: Tepeören Kimya Sanayicileri O.S.B, Tem Yanyol F1 Blok
District and Country: 34956 Istanbul (Tuzla)
TURKEY
Tel. +90 216-5930727
Fax +90 216-5931850

e-mail address of the competent person

responsible for the Safety Data Sheet: help@kayalarkimya.com.tr
Product distribution by: Kayalar Kimya San. Ve Tic. A.S.

1.4. Emergency telephone number

For urgent inquiries refer to: +90 216-5930727 ; HEADQUARTERS: KAYALAR KIMYA SAN.VE TIC. A.Ş. TURKEY
TEL:+90 216-5930727 / SPAIN OFFICE: KAYALAR KIMYA ESPANA S.L. TEL:952206183
MOBILE:665656580 / INSTITUTO NACIONAL DE TOXICOLOGIA TEL: 915620420

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:

Danger

Hazard statements:

H225 Highly flammable liquid and vapour.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P312 Call a POISON CENTRE / doctor / . . . if you feel unwell.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/ national/ international regulation.

Contains: TOLUENE
N-BUTYL ACETATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
TOLUENE		
CAS 108-88-3	$20 \leq x < 30$	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336
EC 203-625-9		
INDEX 601-021-00-3		

Reg. no : 01-2119471310-51-XXXX



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 3/18
Replaced revision:9 (Dated: 31/05/2018)

XYLENE (MIXTURE OF ISOMERS)

CAS 1330-20-7 $20 \leq x < 30$ Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315,
Classification note according to Annex VI to the CLP Regulation: C
EC 215-535-7
INDEX 601-022-00-9
Reg. no : 01-2119488216-32-XXXX

N-BUTYL ACETATE

CAS 123-86-4 $4 \leq x < 5$ Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC 204-658-1
INDEX 607-025-00-1
Reg. no : 01-2119485493-29-XXXX

TRIETHYLAMINE

CAS 121-44-8 $0,3 \leq x < 0,35$ Flam. Liq. 2 H225, Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4
H332, Skin Corr. 1A H314, Eye Dam. 1 H318, STOT SE 3 H335
EC 204-469-4
INDEX 612-004-00-5

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.
SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.
INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 4/18
Replaced revision:9 (Dated: 31/05/2018)

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 5/18
Replaced revision:9 (Dated: 31/05/2018)

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

ZINC STEARATE

Safety glasses, adequate ventilation.

8.1. Control parameters

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2017
GBR	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República I 26; 2012-02-06
ROU	România	Monitorul Oficial al României 44; 2012-01-19
TUR	Türkiye	KİMYASAL MADDELERLE ÇALIŞMALARDA SAĞLIK VE GÜVENLİK ÖNLEMLERİ HAKKINDA YÖNETMELİK - Resmi Gazete Tarihi: 12.08.2013 Resmi Gazete Sayısı: 28733
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2018

TOLUENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	150		300		
VLA	ESP	192	50	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
VLEP	ITA	192	50			SKIN
NDS	POL	100		200		
VLE	PRT	192	50	384	100	SKIN
TLV	ROU	192	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH		75,4	20			

XYLENE (MIXTURE OF ISOMERS)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221		442		SKIN

**KAYALAR KIMYA SAN.VE TIC.A.S.**Revision nr. 10
Dated 06/11/2018**VP850.77.0000
POLYURETHANE VARNISH SEALER**Printed on 28/02/2020
Page n. 6/18
Replaced revision:9 (Dated: 31/05/2018)

VLA	ESP	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	
VLEP	ITA	221	50	442	100	SKIN
NDS	POL	100				
VLE	PRT	221	50	442	100	SKIN
TLV	ROU	221	50	442	100	SKIN
ESD	TUR	221	50	442	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

**N-BUTYL ACETATE
Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV	BGR	710		950	
VLA	ESP	724	150	965	200
WEL	GBR	724	150	966	200
NDS	POL	200		950	
TLV	ROU	715	150	950	200
TLV-ACGIH			50		150

**TRIETHYLAMINE
Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	8,4		12,6		SKIN
VLA	ESP	8,4	2	12,6	3	SKIN
WEL	GBR	8	2	17	4	SKIN
VLEP	ITA	8,4	2	12,6	3	SKIN
NDS	POL	3		9		
VLE	PRT	8,4	2	12,6	3	SKIN
TLV	ROU	8,4	2	12,6	3	SKIN
ESD	TUR	8,4	2	12,6	3	SKIN
OEL	EU	8,4	2	12,6	3	SKIN
TLV-ACGIH			0,5		1	SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 7/18
Replaced revision:9 (Dated: 31/05/2018)

When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	viscous liquid
Colour	yellowish
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	> 35 °C
Boiling range	Not available
Flash point	< 23 °C
Evaporation Rate	Not available
Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10

Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020

Page n. 8/18

Replaced revision:9 (Dated: 31/05/2018)

Vapour density	Not available
Relative density	0,99 ± 0,03 Kg/l
Solubility	soluble in organic solvents
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Kinematic (40 °C): >20,5 mm ² /s
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

VOC (Directive 2004/42/EC) : 56,02 % - 554,61 g/litre

SECTION 10. Stability and reactivity

ZINC STEARATE

Stable. Incompatible with strong oxidizing agents.

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

TOLUENE

Avoid exposure to: light.

N-BUTYL ACETATE

Decomposes on contact with: water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds.May form explosive mixtures with: air.May react dangerously with: strong oxidising agents,strong acids,sulphur.

XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10

Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020

Page n. 9/18

Replaced revision:9 (Dated: 31/05/2018)

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

N-BUTYL ACETATE

Avoid exposure to: moisture,sources of heat,naked flames.

10.5. Incompatible materials

N-BUTYL ACETATE

Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

ZINC STEARATE

Respiratory irritant. Typical TLV / STEL 10 mg/m3.

Toxicity data

ORL-RAT LD50 > 10000 mg kg-1

ORL-MUS LD50 > 10000 mg kg-1

IPR-MUS LD50 354 mg kg-1

.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 10/18
Replaced revision:9 (Dated: 31/05/2018)

XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.
POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

XYLENE (MIXTURE OF ISOMERS)

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects

TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

XYLENE (MIXTURE OF ISOMERS)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

>2000 mg/kg



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 11/18
Replaced revision:9 (Dated: 31/05/2018)

XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral) 3523 mg/kg Rat

LD50 (Dermal) 4350 mg/kg Rabbit

LC50 (Inhalation) 26 mg/l/4h Rat

TOLUENE

LD50 (Oral) 5580 mg/kg Rat

LD50 (Dermal) 12124 mg/kg Rabbit

LC50 (Inhalation) 28,1 mg/l/4h Rat

N-BUTYL ACETATE

LD50 (Oral) > 6400 mg/kg Rat

LD50 (Dermal) > 5000 mg/kg Rabbit

LC50 (Inhalation) 21,1 mg/l/4h Rat

TRIETHYLAMINE

LD50 (Oral) 460 mg/kg Rat

LD50 (Dermal) 580 mg/kg Rabbit

LC50 (Inhalation) 14,5 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10

Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020

Page n. 12/18

Replaced revision:9 (Dated: 31/05/2018)

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999). The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

XYLENE (MIXTURE OF ISOMERS)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC). The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: Kinematic (40°C): >20,5 mm²/s

SECTION 12. Ecological information

12.1. Toxicity

Information not available

12.2. Persistence and degradability

XYLENE (MIXTURE OF ISOMERS)

Solubility in water

100 - 1000 mg/l

Degradability: information not available

TOLUENE

**VP850.77.0000
POLYURETHANE VARNISH SEALER**

Solubility in water 100 - 1000 mg/l

Rapidly degradable

N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

TRIETHYLAMINE

Solubility in water > 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential**XYLENE (MIXTURE OF ISOMERS)**

Partition coefficient: n-octanol/water 3,12

BCF 25,9

TOLUENE

Partition coefficient: n-octanol/water 2,73

BCF 90

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3

BCF 15,3

TRIETHYLAMINE

Partition coefficient: n-octanol/water 1,45

BCF < 0,5

12.4. Mobility in soil**XYLENE (MIXTURE OF ISOMERS)**

Partition coefficient: soil/water 2,73

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

TRIETHYLAMINE

Partition coefficient: soil/water 2,57

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 14/18
Replaced revision:9 (Dated: 31/05/2018)

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 15/18
Replaced revision:9 (Dated: 31/05/2018)

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special Provision: 640D		
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Pass.:	Maximum quantity: 5 L	Packaging instructions: 353
	Special Instructions:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 48 TOLUENE

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 16/18
Replaced revision:9 (Dated: 31/05/2018)

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1A	Skin corrosion, category 1A
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 17/18
Replaced revision:9 (Dated: 31/05/2018)

- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

All ingredients used in the product have REACH registration. The registration numbers are listed below ;

01-2119457861-32-XXXX
01-2119456816-28-XXXX
01-2119473980-30-XXXX
01-2119471310-51-XXXX
01-2119475108-36-XXXX
01-2119475104-44-XXXX
01-2119473985-20-XXXX
01-2119473975-21-XXXX
01-2119485493-29-XXXX
01-2119488216-32-XXXX
01-2119489379-17-XXXX
01-2119475103-46-XXXX
01-2119517580-45-XXXX
01-2119462828-25-XXXX
01-2119458049-33-XXXX
01-2119455536-33-XXXX
01-2119471330-49-XXXX
01-2119486799-10-XXXX
01-2119484609-23-XXXX
01-2119457290-43-XXXX
01-2119452498-28-XXXX



KAYALAR KIMYA SAN.VE TIC.A.S.

Revision nr. 10
Dated 06/11/2018

VP850.77.0000
POLYURETHANE VARNISH SEALER

Printed on 28/02/2020
Page n. 18/18
Replaced revision:9 (Dated: 31/05/2018)

01-2119457017-41-XXXX
01-2119513214-54-XXXX
01-2119539477-28-XXXX
01-2119475791-29-XXXX
01-2119485796-17-XXXX
01-2119379499-16-XXXX
01-2119457857-21-XXXX
01-2119454791-34-XXXX
01-2119457435-35-XXXX
01-2120106403-73-XXXX
01-2119472428-31-XXXX
01-2119457610-43-XXXX
01-2119457561-38-XXXX
01-2119539452-40-XXXX

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 07 / 08 / 09 / 10 / 11 / 12 / 13 / 15.