



## TECHNICAL DATA SHEET

<b>Product Code</b>	<b>KDO</b>
<b>Product description</b>	<b>KEMI DECK OIL</b>

### **COMPOSITION**

- mixture of natural oils reinforced with resins, specific for the finishing of external surfaces, enriched with UV filters, hardwaxes and wood preservatives, almost odorless, very transparent, protects all types of wood. Ready to use.

### **DESCRIPTION**

- Special formula that combines the natural properties of oils and the resistance of resins. Quick, resistant and decorative. Suitable for all outdoor surfaces, terraces, coverings, furnishings and windows. Recommended as a finish, it can also be used as a single product in two or three coats.

### **APPLICATION**

- On the sanded, clean and degreased substrate, apply the product evenly with a brush, roller or rag, avoiding creating excesses. Leave to dry for 8 to 12 hours. For a soft touch effect, sand with 220/240 grit and remove dust. Proceed to apply a second coat. Total drying 24h. If desired, a third coat can be applied.

Application	Brush, roller, cloth
Packaging	6x1 L – 2x5 L – 1x20 L

### **CHEMICAL AND PHYSICAL PROPERTIES ( standard value )**

Aspect	Transparent
Specific weight at 20°C	0,88 kg/lt
Flash Point	>60° C

Shelf Life : 12 months at 20°C in original pack

Safety advises: see information in the safety data sheet