
PRODUCT INFORMATION



Diamant 3000 Ultra Cut

Application area:

Silicone-free intensive rubbing compound for professionals.

Product description:

Diamant 3000 Super Cut is a silicone-free professional, intensive rubbing compound with an extremely strong mix of abrasive grinding components. Thermally optimised aluminium oxide micro-particles ensure reliable defect correction with very simple machine guidance. After starting polishing, the cut immediately achieves, and leaves, a reduced hologram and homogeneously uniform gloss. Dust-free processing and effortless removal of polishing residues ("easy-off"). Removes grind sections up to 2,000 grit.

Features:

- extremely simple to apply
- with high-end abrasives
- free of silicone

Application:

Polytop Diamant rubbing compounds are applied best by a rotation polishing machine. Apply the Diamant 3000 evenly onto the POLYTOP polishing pad and process crosswise in sections on the paint surface. Polishing residues can be rubbed off by a microfiber cloth. Using a Polytop polishing fleece has a double or triple abrasiveness compared to a polishing sponge.

POLYTO

Additional information:

Shake well before use! Protect against frost! Safety data sheet for professional users available under www.polytop.de.

Ingredients:

EC 648/2004: aliphatic hydrocarbons 15-30%, anionic surfactants less than 5%, nonionic surfactants less than 5%, preservatives (PHENOXYETHANOL, LAURYLAMINE DIPROPYLENEDIAMINE, BUTYLBENZISOTHIAZOLINONE), additional information: paraffinum liquidum, abrasives, thickener

Hazardous informations:

Safety data sheet available on request

Density:

1,10

Art. no.:	Pack size:	
17300001	1	Liter
17300250	0,25	Liter